


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:  
County: Ford  
Distance and direction from nearest town or city street address of well if located within city?  
2305 West Wyatt Earp, Dodge City, KS.

2 WATER WELL OWNER: Byron Winans  
RR#, St. Address, Box #: P.O. Box 446  
City, State, ZIP Code: Dodge City, Ks. 67801  
Board of Agriculture, Division of Water Resources  
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
  
1 Mile

4 DEPTH OF COMPLETED WELL: 55' ft. ELEVATION:  
Depth(s) Groundwater Encountered 1. 38' ft. 2. ft. 3. ft.  
WELL'S STATIC WATER LEVEL 37.25 ft. below land surface measured on mo/day/yr 11-12-96  
Pump test data: Well water was ft. after hours pumping gpm  
Est. Yield gpm; Well water was ft. after hours pumping gpm  
Bore Hole Diameter 8 1/2" in. to 55' ft., and in. to ft.  
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well  
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) Air Sprayer  
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well  
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted  
Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:  
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped  
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded  
Blank casing diameter 2.375 in. to 52' ft. Dia. in. to ft. Dia. in. to SDR 13 ft.  
Casing height above land surface Flush Mt. in., weight lbs./ft. Wall thickness or gauge No. Sch 40  
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement  
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)  
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  
SCREEN OR PERFORATION OPENINGS ARE:  
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
3 Torch cut 10 Other (specify)  
SCREEN-PERFORATED INTERVALS: From 52' ft. to 54 1/2' ft. From ft. to ft.  
From ft. to ft. From ft. to ft.  
GRAVEL PACK INTERVALS: From 55' ft. to 50' ft. From ft. to ft.  
From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
Grout Intervals: From 50' ft. to 37' ft. From 37' ft. to 0' ft. From ft. to ft.  
What is the nearest source of possible contamination:  
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
13 Insecticide storage  
Direction from well? South How many feet? 20'

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-12-96 and this record is true to the best of my knowledge and belief. Kansas  
Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 11-16-96  
under the business name of JB Environmental Drilling by (signature) James Buerk

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

R

EW

SEC

1/4

1/4

1/4