


HWS19

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: Ford		Fraction: NE 1/4 SE 1/4 SW 1/4	Section Number: 27	Township Number: T 26 S	Range Number: R 25 E																																				
Distance and direction from nearest town or city street address of well if located within city? 2305 West Wyatt Earp, Dodge City, KS.																																									
2 WATER WELL OWNER: Byron Winans RR#, St. Address, Box #: P.O. Box 446 City, State, ZIP Code: Dodge City, Ks. 67801 Board of Agriculture, Division of Water Resources Application Number:																																									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 50' ft. ELEVATION: Depth(s) Groundwater Encountered: 1. 38' ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL: 37.02 ft. below land surface measured on mo/day/yr 11-14-96 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter: 8 1/2" in. to 50' ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No																																							
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 2.375 in. to 30' ft. Dia. in. to ft. Dia. in. to SDR 13 ft. Casing height above land surface Flush Ht. in. weight lbs./ft. Wall thickness or gauge No. Sch. 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) 7 Torch cut SCREEN-PERFORATED INTERVALS: From 50' ft. to 30' ft. From ft. to ft. GRAVEL PACK INTERVALS: From 50' ft. to 28' ft. From ft. to ft. From ft. to ft. From ft. to ft.																																									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 28' ft. to 4' ft. From 4' ft. to 0' ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? South How many feet? 140'																																									
<table border="1"><thead><tr><th>FROM</th><th>TO</th><th>LITHOLOGIC LOG</th><th>FROM</th><th>TO</th><th>PLUGGING INTERVALS</th></tr></thead><tbody><tr><td>0</td><td>4.50</td><td>Grass-dk brn clay, root frag. moist-dry, few pebbles, no odor.</td><td></td><td></td><td></td></tr><tr><td>4.50</td><td>16</td><td>Med-dk brn silty clay, moist, low plasticity, no odor.</td><td></td><td></td><td></td></tr><tr><td>16</td><td>25</td><td>Med brn sandy clay, moist, firm.</td><td></td><td></td><td></td></tr><tr><td>25</td><td>35</td><td>Brn fine-coarse sand & gravel, dry no odor, poorly sorted. Moist to wet at 35', no odor.</td><td></td><td></td><td></td></tr><tr><td>35</td><td>50</td><td>Fine-coarse sand & gravel, wet w/ pebbles & cobbles, poorly sorted, subrounded, none to faint odor.</td><td></td><td></td><td></td></tr></tbody></table>						FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0	4.50	Grass-dk brn clay, root frag. moist-dry, few pebbles, no odor.				4.50	16	Med-dk brn silty clay, moist, low plasticity, no odor.				16	25	Med brn sandy clay, moist, firm.				25	35	Brn fine-coarse sand & gravel, dry no odor, poorly sorted. Moist to wet at 35', no odor.				35	50	Fine-coarse sand & gravel, wet w/ pebbles & cobbles, poorly sorted, subrounded, none to faint odor.			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																				
0	4.50	Grass-dk brn clay, root frag. moist-dry, few pebbles, no odor.																																							
4.50	16	Med-dk brn silty clay, moist, low plasticity, no odor.																																							
16	25	Med brn sandy clay, moist, firm.																																							
25	35	Brn fine-coarse sand & gravel, dry no odor, poorly sorted. Moist to wet at 35', no odor.																																							
35	50	Fine-coarse sand & gravel, wet w/ pebbles & cobbles, poorly sorted, subrounded, none to faint odor.																																							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-14-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 11-16-96 under the business name of JB Environmental Drilling by (signature) James Beck																																									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.																																									

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4