

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Ford		SW 1/4 SE 1/4 SW 1/4	27	T 26 S	R 25 E (W)
Distance and direction from nearest town or city street address of well if located within city? 2305 West Wyatt Earp, Dodge City, KS.					
2 WATER WELL OWNER: Byron Winans					
RR#, St. Address, Box #: P.O. Box 446					
City, State, ZIP Code: Dodge City, Ks. 67801					
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 49 1/2' ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 34' ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 37.08 ft. below land surface measured on mo/day/yr 11-14-96			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 8 1/2" in. to 50' ft. and in. to ft.			
		WELL WATER TO BE USED AS:			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No (X)			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded X					
Blank casing diameter 2.375 in. to 29 1/2' ft. Dia. in. to ft. Dia. in. to SDR 13 ft.					
Casing height above land surface: Flush Mt. in. weight lbs./ft. Wall thickness or gauge No. Sch 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 49 1/2' ft. to 29 1/2' ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 50' ft. to 28' ft. From ft. to ft.					
6 GROUT MATERIAL:					
1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 28' ft. to 4' ft. From 4' ft. to 0' ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage					
Direction from well? West How many feet? 200'					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Cobbles, gravel road pack, hard.			
1	11	Dl brn clay, dry, no odor.			
11	16	Med-lt brn silty clay, moist, no odor, trace of caliche stringers.			
16	21	Med brn silty clay w/ trace of ls.rx. grains, moist, no odor.			
21	23	Dk brn clay, moist-damp, no odor.			
23	24	Gray clayey sand, soft, no odor.			
24	29	Fine-coarse sand, dry, no odor.			
29	35	Pale gray fine-coarse sand, moist, faint-mod. odor. Wet at 34'.			
35	40	Pale gray sand & gravel, wet, mod. to faint odor, poorly sorted.			
40	49.5	Tan fine-coarse sand, wet, poorly sorted.			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-13-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 11-16-96 under the business name of JB Environmental Drilling by (signature) James Beebe					