

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Ford</u>		<u>SW 1/4 SE 1/4 SE 1/4</u>	<u>35</u>	<u>T 26 S</u>	<u>R 25 E/W</u>
Distance and direction from nearest town or city street address of well if located within city? <u>718 S. Second Ave</u>					
2 WATER WELL OWNER: <u>Southwest Oil & Supply Co. VE8</u>					
RR#, St. Address, Box #: <u>718 S. Second Ave</u>					
City, State, ZIP Code: <u>Dodge City, Kansas 67801</u>					
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>29</u> ft. ELEVATION: <u>2479.01</u>			
		Depth(s) Groundwater Encountered <u>1 DRY WELL</u> ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>0</u> ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter <u>10</u> in. to <u>29</u> ft. and in. to ft.			
WELL WATER TO BE USED AS:					
5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only <u>10</u> Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes <u>No</u>					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped <u>2</u> PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter <u>4</u> in. to <u>19</u> ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface <u>3.84</u> in., weight lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass <u>7</u> PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: <u>1</u> Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes SCREEN-PERFORATED INTERVALS: From <u>19</u> ft. to <u>29</u> ft. From ft. to ft. GRAVEL PACK INTERVALS: From <u>17</u> ft. to <u>29</u> ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout <u>3</u> Bentonite 4 Other					
Grout Intervals: From <u>0</u> ft. to <u>17</u> ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy <u>11</u> Fuel storage 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below)					
Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	Medium Sand			
4	12	Sandy Clay			
12	25	Sand w/ pebbles			
25	29	Medium Sand			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1)</u> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>5-8-96</u> and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. <u>534</u> This Water Well Record was completed on (mo/day/yr) <u>7-12-96</u>					
under the business name of <u>PSI</u> by (signature) <u>Barton Reese</u>					