

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: FORD		SE 1/4 SE 1/4 SE 1/4		35		T 26 S		R 25 EW	
Distance and direction from nearest town or city street address of well if located within city? 718 S. Second Ave									
2 WATER WELL OWNER: Southwest Oil + Supply Co.									
RR#, St. Address, Box # : 718 S. Second Ave.									
City, State, ZIP Code : Dodge City, KS 67801									
Board of Agriculture, Division of Water Resources Application Number: MW-13									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 45 ft. ELEVATION: 2478.12							
		Depth(s) Groundwater Encountered 1. 33.69 ft. 2. 33.69 ft. 3. 33.69 ft.							
		WELL'S STATIC WATER LEVEL 33.69 ft. below land surface measured on mo/day/yr 10-12-94							
		Pump test data: Well water was 45 ft. after 10 hours pumping 10 gpm							
		Est. Yield 45 gpm: Well water was 45 ft. after 10 hours pumping 10 gpm							
		Bore Hole Diameter 8 in. to 45 ft., and 45 in. to 45 ft.							
		WELL WATER TO BE USED AS:							
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well							
		Was a chemical/bacteriological sample submitted to Department? Yes.....No..... If yes, mo/day/yr sample was submitted							
		Water Well Disinfected? Yes No							
5 TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 2 in. to 45 ft., Dia 45 in. to 45 ft., Dia 45 in. to 45 ft. Casing height above land surface 6.84 in., weight 8.4 lbs./ft. Wall thickness or gauge No. 8.4 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 30 ft. to 45 ft., From 30 ft. to 45 ft., From 30 ft. to 45 ft., From 30 ft. to 45 ft.									
GRAVEL PACK INTERVALS: From 29 ft. to 45 ft., From 29 ft. to 45 ft., From 29 ft. to 45 ft., From 29 ft. to 45 ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout Intervals: From 0 ft. to 29 ft., From 29 ft. to 45 ft., From 29 ft. to 45 ft., From 29 ft. to 45 ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage									
Direction from well? How many feet?									
FROM		TO		LITHOLOGIC LOG		FROM		TO	
0		5		medium sand					
5		14		silty clay					
14		24		med. coarse sand					
24		30		silty sand					
30		45		coarse-med. sand					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-28-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 534 This Water Well Record was completed on (mo/day/yr) 2-17-97 under the business name of PSI by (signature) <i>[Signature]</i>									