

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Ford	NW ¼ NW ¼ SW ¼	12	T 26 S	R 25 E/W

Distance and direction from nearest town or city street address of well if located within city?

North on Ave. A 1 ¼ miles

2 WATER WELL OWNER: Dale Gabel	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: 1706 Wooden Road	Application Number:
City, State, ZIP Code: Dodge City, Kansas 67801	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 165 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 7.5 ft. below land surface measured on mo/day/yr 8-3-90 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 12 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 12 in. to 165 ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No XX; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes XX No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued XX Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 5 in. to 165 ft. Dia			Threaded
Casing height above land surface 12 in. weight 200 psi			lbs./ft. Wall thickness or gauge No. SDR 21
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 120 ft. to 160 ft.	From ft. to ft.	
GRAVEL PACK INTERVALS:	From 35 ft. to 165 ft.	From ft. to ft.	

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other hole plug
Grout Intervals:	From 5 ft. to 35 ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.
What is the nearest source of possible contamination:	none - new bldg. site	10 Livestock pens	14 Abandoned water well	
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	
Direction from well?		How many feet?		

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	20	Top soil & clay			
20	40	Clay & fine sand			
40	70	Sand rock & fine sand			
70	80	Clay			
80	100	Clay & cleechie			
100	120	Cleechie & fine sand			
120	140	Fine sand			
140	155	Fine sand & some medium sand			
155	180	Clay & rock layers			
180	200	" "			
200	240	Gray clay & rock layers			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-3-90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 179 This Water Well Record was completed on (mo/day/yr) 8-22-90 under the business name of Joe's Well Service, Inc. Cimarron, Ks. by (signature) David Cisk
--