


1 LOCATION OF WATER WELL: Fraction SW 1/4 SW 1/4 SW 1/4 Section Number 25 Township Number T 26 S Range Number R 25 EW

Distance and direction from nearest town or city street address of well if located within city?  
 100 Military - Dodge City, Kansas

2 WATER WELL OWNER: Frank Epp  
 RR#, St. Address, Box #: 100 Military Plaza Board of Agriculture, Division of Water Resources  
 City, State, ZIP Code: Dodge City, Kansas 67801 Application Number: 213.45

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
  
 4 DEPTH OF COMPLETED WELL: 87 ft. ELEVATION: 213.45  
 Depth(s) Groundwater Encountered: 1. 144.90 ft. 2. ft. 3. ft.  
 WELL'S STATIC WATER LEVEL: 68.55 ft. below land surface measured on mo/day/yr 12/3/92  
 Pump test data: Well water was ft. after hours pumping gpm  
 Est. Yield gpm: Well water was ft. after hours pumping gpm  
 Bore Hole Diameter: 6 5/8 in. to 88.0 ft. and in. to ft.  
 WELL WATER TO BE USED AS:  
 5 Public water supply 8 Air conditioning 11 Injection well  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well MW-1  
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped  
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X  
 Threaded X  
 Blank casing diameter 2 in. to 87.0 ft. Dia. in. to ft. Dia. in. to Sch. 40 ft.  
 Casing height above land surface 0 in., weight lbs./ft. Wall thickness or gauge No.  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)  
 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 67.0 10 Other (specify)  
 SCREEN-PERFORATED INTERVALS: From 87.0 ft. to 67.0 ft. From ft. to ft.  
 GRAVEL PACK INTERVALS: From 88.0 ft. to 65.0 ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
 Grout Intervals: From 65.0 ft. to 61.0 ft. From 61.0 ft. to 0.0 ft. From ft. to ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 13 Insecticide storage  
 Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	10"	Silty, Tan, Dry			
10'	20	Sand, Tan, Fine Grained, Some Gravel			
20	25	Caliche, White, Sand Med. to Large			
25	30	Sand, Tan, Fine Grained, Some Gravel			
30	40	Sand, Tan, Fine Grained			
40	45	Clay, Tan, Lean			
45	88	Sand, Tan, Fine Grained, Clay, Tan, Lean			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/22/92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 540 This Water Well Record was completed on (mo/day/yr) 12/9/92 under the business name of Prairie Land Environmental Remediation, Inc. (signature)

OFFICE USE ONLY  
T  
R  
EW  
SEC.