


LOCATION OF WATER WELL: County: Ford Fraction: SW 1/4 SW 1/4 SW 1/4 Section Number: 25 Township Number: T 26 S Range Number: R 25 EW

Distance and direction from nearest town or city street address of well if located within city? South of Wyatt Earp Blvd. & B Ave.

WATER WELL OWNER: Unknown - Work performed for: Taylor & Associates RR#, St. Address, Box #: 509 N. 6th Board of Agriculture, Division of Water Resources City, State, ZIP Code: Garden City, Ks. 67846 Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



DEPTH OF COMPLETED WELL: 35' ft. ELEVATION:

Depth(s) Groundwater Encountered: 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL: 28' ft. below land surface measured on mo/day/yr 7/28/88. Pump test data: Well water was ... ft. after ... hours pumping ... gpm Est. Yield: 11 gpm: Well water was ... ft. after ... hours pumping ... gpm Bore Hole Diameter: 7.7/8" in. to ... 33' ft. and ... in. to ... ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes ... No ... X ... If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X

TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded X 7 Fiberglass

Blank casing diameter: 4 in. to 33 ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface: 18 in. weight: 2.08 lbs./ft. Wall thickness or gauge No. 237

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 18-33 ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 15-33 ft. to ft. From ft. to ft. From ft. to ft.

GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 15 ft. From ft. to ft. From ft. to ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage None observed

Direction from well? How many feet?

LITHOLOGIC LOG table with columns FROM, TO, LITHOLOGIC LOG, FROM, TO, LITHOLOGIC LOG. Rows include: 0-1 Silty clay, 1-26 Brown clay, 26-33 Sand fine to medium coarse. Small to large gravel and few cobble stones, 33-35 Tan clay.

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/29/88 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 145 This Water Well Record was completed on (mo/day/yr) 8/10/88 under the business name of Henkle Drilling & Supply Company, Inc. by (signature) Bruce J. Reckmuth