

1 LOCATION OF WATER WELL: County: FORD	Fraction NE 1/4 SE 1/4 SW 1/4	Section Number 28	Township Number T 26 S	Range Number R 25 E/W
---	----------------------------------	----------------------	---------------------------	--------------------------

Distance and direction from nearest town or city street address of well if located within city?

1/2 East of Dodge City, Kansas

2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :	Corky Behee W. Park Dodge City, Kansas 67801	Board of Agriculture, Division of Water Resources Application Number: ---
---	--	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 160 ft. ELEVATION: Slope
	Depth(s) Groundwater Encountered 1. Not available ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 32 ft. below land surface measured on mo/day/yr July 22, 1991 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 30 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 10 in. to 160 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well XXX Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes XX No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued XX Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
XXX 2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 5 in. to 140 ft., Dia	2.8 in. to ft., Dia	lbs./ft. Wall thickness or gauge No. 265	
Casing height above land surface 18 in., weight			
TYPE OF SCREEN OR PERFORATION MATERIAL:	XX PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	XX Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 140 ft. to 160 ft.		
GRAVEL PACK INTERVALS:	From 34 ft. to 160 ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	XX Bentonite	4 Other
Grout Intervals:	From 0 ft. to 34 ft.			
What is the nearest source of possible contamination:	XX Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	14 Abandoned water well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	15 Oil well/Gas well
Direction from well?	North			16 Other (specify below)
				How many feet? 100

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Topsoil			
3	11	Clay			
11	34	Large Sand			
34	101	Clay and Med. Sand 50/50			
101	151	Med. Sand			
151	153	Clay			
153	160	Med. Sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) July 27, 1991 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 252 This Water Well Record was completed on (mo/day/year) August 6, 1991 under the business name of Friesen Windmill & Supply Inc. by (signature)
---

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

9620921006-22