


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Ford	NW 1/4 NW 1/4 NE 1/4	29	T 26 S	R 25 EW

Distance and direction from nearest town or city street address of well if located within city?

From Dodge City, Ks. - 2 miles West on highway 50

2 WATER WELL OWNER: Jerry Kilingschmidt	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: % Debra Stasch	Application Number:
City, State, ZIP Code: 105 Cambridge Court - Garden City, Ks. 67846	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 158 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL: 17 ft. below land surface measured on mo/day/yr Dec. 5, 1986
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield 7.5 gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter: 8 in. to 158 ft., and in. to ft.
	WELL WATER TO BE USED AS:
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
	Was a chemical/bacteriological sample submitted to Department? Yes No XXX; If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes XXX No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued XXX Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter: 5 in. to 158 ft., Dia			
Casing height above land surface: 12 in., weight SDR 200 21 lbs./ft. Wall thickness or gauge No. 200 psi			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 132 ft. to 152 ft.		
	From ft. to ft.		
GRAVEL PACK INTERVALS:	From 45 ft. to 158 ft.		
	From ft. to ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 5 ft. to 45 ft.				
What is the nearest source of possible contamination:	none (new bldg. site)	10 Livestock pens	14 Abandoned water well	
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	

Direction from well?	How many feet?				
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	15	Top soil, clay (5 ft.) & medium to coarse sand			
15	30	Coarse sand & gravel			
30	45	Coarse sand & gravel with clay			
45	60	Clay			
60	75	Clay & fine sand			
75	90	Fine sand			
90	105	Fine sand & clay layers			
105	120	Fine sand			
120	135	Fine to medium with coarse sand (very loose)			
135	155	Very coarse sand & sand (loose)			
155	165	Clay & blue shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) April 24, 1987 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 179 This Water Well Record was completed on (mo/day/yr) April 30, 1987 under the business name of Joe's Well Service, Inc. Cimarron, Ks. by (signature) David Crick
--

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks. underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.