

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: FORD		SE 1/4 SE 1/4 SE 1/4		34		T 26 S		R 25	
Distance and direction from nearest town or city street address of well if located within city? 1/4 Mile West of Dodge City, Kansas									
2 WATER WELL OWNER:		J & K Ranch, Mr. Joe Berkely				Well #2			
RR#, St. Address, Box # :		1909 LaMesa				Board of Agriculture, Division of Water Resources			
City, State, ZIP Code :		Dodge City, Kansas 67801				Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 160 ft. ELEVATION: Slope							
		Depth(s) Groundwater Encountered 1. Not available ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 25 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield 20 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 9.7/8 in. to 160 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well XX Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No XX; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes XX No							
		5 TYPE OF BLANK CASING USED:							
		1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued XX Clamped XX PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded							
		Blank casing diameter 5 in. to 120 ft., Dia. in. to ft., Dia. in. to ft.							
		Casing height above land surface 18 in., weight 2.8 lbs./ft. Wall thickness or gauge No. 265							
TYPE OF SCREEN OR PERFORATION MATERIAL:		XX PVC							
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement		11 Other (specify)							
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped XX Saw cut 11 None (open hole)							
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes									
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS:		From 120 ft. to 160 ft., From ft. to ft.							
GRAVEL PACK INTERVALS:		From 14 ft. to 160 ft., From ft. to ft.							
6 GROUT MATERIAL:		XX Neat cement 2 Cement grout 3 Bentonite 4 Other							
Grout Intervals:		From 4 ft. to 14 ft., From ft. to ft., From ft. to ft.							
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well							
XX Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		12 Fertilizer storage 16 Other (specify below)							
2 Sewer lines 5 Cess pool 8 Sewage lagoon 13 Insecticide storage									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard									
Direction from well? West		How many feet? 500							
FROM	TO	LITHOLOGIC LOG		FROM	TO	LITHOLOGIC LOG			
0	5	Clay							
5	18	Fine Sand							
18	23	Med. to Lar. Sand							
23	98	Clay w/Sand Strip							
98	160	Med. to Lar. Sand & Gravel							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) June 6, 1985 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 252 This Water Well Record was completed on (mo/day/year) June 24, 1985 under the business name of FRIESEN WINDMILL & SUPPLY INC. by (signature)									
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.									

3393073068-40