


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Ford		SW 1/4 NE 1/4 SE 1/4	35	T 26 S	R 25 EW
Distance and direction from nearest town or city street address of well if located within city? Approx. 440' North & 156' West of Intersection of South 2nd & Market Streets, Dodge City, KS 01948003 MW-10					
2 WATER WELL OWNER: FINA Oil & Chemical Company RR#, St. Address, Box # : P.O. Box 2159 City, State, ZIP Code : Dallas, TX 75221 Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 24.5 ft. ELEVATION: Approx. Surface Elev.: 2478.9			
<div style="text-align: center;">N 1 Mile W E S</div> 		Depth(s) Groundwater Encountered 1. 20 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 20.40 ft. below land surface measured on mo/day/yr 02/03/94			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield N/A gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 8.25 in. to 24.5 ft. and in. to ft.			
TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile			
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)			
Blank casing diameter 2 in. to 14.5 ft. Dia in. to ft. Dia in. to ft.		7 Fiberglass Threaded X			
Casing height above land surface -0.66 in., weight lbs./ft. Wall thickness or gauge No. Schedule 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)		12 None used (open hole)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		10 Other (specify)			
2 Louvered shutter 4 Key punched 7 Torch cut					
SCREEN-PERFORATED INTERVALS: From 14.5 ft. to 24.5 ft. From ft. to ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 12.5 ft. to 24.5 ft. From ft. to ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 10.5 ft. From 10.5 ft. to 12.5 ft. From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		12 Fertilizer storage 16 Other (specify below)			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 13 Insecticide storage					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard					
Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0.0	3.0	Sandy Fat Clay; Brown			
3.0	7.0	Fine Sand; Tan			
7.0	13.5	Fine to Coarse Sand; Tan			
13.5	14.5	Sandy Silt; Brown			
14.5	25.0	Coarse Sand; Brown			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 02/02/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 03/22/94 under the business name of Terracon Consultants, Inc. by (signature) Steve Fischer					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					