

1 LOCATION OF WATER WELL:		Fraction		Form WWC-5		KSA 82a-1212	
County: Ford		SW 1/4 SE 1/4 SE 1/4		Section Number		Township Number	
				35		T 26 S	
Distance and direction from nearest town or city street address of well if located within city?						Range Number	
118 S. 2nd, Dodge City, Ks.						R 25 E	
2 WATER WELL OWNER: Southwest Oil						MW#6	
RR#, St. Address, Box # : P. O. Box 116						Board of Agriculture, Division of Water Resources	
City, State, ZIP Code : Dodge City, Ks. 67801						Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 32 ft.		ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.		WELL'S STATIC WATER LEVEL 2.0 ft. below land surface measured on mo/day/yr 11/13/89			
		Pump test data: Well water was ft. after hours pumping gpm		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 8 3/4 in. to 32 ft. and in. to ft.		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well		Was a chemical/bacteriological sample submitted to Department? Yes No X			
		Water Well Disinfected? Yes No X					
5 TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR)		6 Asbestos-Cement 9 Other (specify below)		Welded			
2 PVC 4 ABS		7 Fiberglass		Threaded X			
Blank casing diameter 2 in. to 32 ft. Dia in. to ft. Dia in. to ft.							
Casing height above land surface 2 in. weight 703 lbs./ft. Wall thickness or gauge No. 154							
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)							
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes							
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)							
SCREEN-PERFORATED INTERVALS: From 17 ft. to 32 ft. From ft. to ft.							
GRAVEL PACK INTERVALS: From 10 ft. to 32 ft. From ft. to ft.							
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other							
Grout Intervals: From 0 ft. to 3 ft. From 3 ft. to 7 ft. From ft. to ft.							
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well					
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well							
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)							
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage							
Direction from well? Immediate area							
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS							
0 1 Fill sand.							
1 3 Fine sand.							
3 12 Brown clay.							
12 32 Fine to coarse sand, small to large gravel.							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/13/89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 145 This Water Well Record was completed on (mo/day/yr) 5/21/90 under the business name of Henkle Drilling & Supply Co., Inc. by (signature) [Signature]							
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.							