


1 LOCATION OF WATER WELL: Fraction NE 1/4 NW 1/4 NE 1/4 Section Number 36 Township Number T 26 S Range Number R 25 EW
 County: Ford
 Distance and direction from nearest town or city street address of well if located within city?

600 East Trail - Dodge City, KS.

67801

2 WATER WELL OWNER: Safety - Kleen
 RR#, St. Address, Box # :
 City, State, ZIP Code : (See above)
 Board of Agriculture, Division of Water Resources
 Application Number: N/A

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 30.8' ft. ELEVATION: GL

Depth(s) Groundwater Encountered 1. 18.4' ft. 2. 18.4' ft. 3. 3 1/2' / 90 ft.

WELL'S STATIC WATER LEVEL 18.4' ft. below land surface measured on mo/day/yr 3/2/90

Pump test data: Well water was N/A ft. after N/A hours pumping N/A gpm

Est. Yield N/A gpm: Well water was N/A ft. after N/A hours pumping N/A gpm

Bore Hole Diameter 10.75 in. to 30.8' ft., and N/A in. to N/A ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well ✓

Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No ✓

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped

1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Threaded ✓

2 PVC 4 ABS 7 Fiberglass

Blank casing diameter 10.8' in. to 10.8' ft., Dia 10.8' in. to 10.8' ft., Dia 10.8' in. to 10.8' ft.

Casing height above land surface GL in., weight Sch 40 lbs./ft. Wall thickness or gauge No. Sch 40

TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement

1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

1 Continuous slot 3 Mill slot Wire wrapped 9 Drilled holes

2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 10.8' ft. to 30.8' ft., From 10.8' ft. to 30.8' ft.

GRAVEL PACK INTERVALS: From 8.8' ft. to 30.8' ft., From 8.8' ft. to 30.8' ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 0 ft. to 6' ft., From 0 ft. to 6' ft., From 0 ft. to 6' ft.

What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well

1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Hydrocarbon spill (on site)

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4.3	Dark br. Clay loam			
4.3	7.0	br. clay grading to VF Sand			
7.0	9.3	Sand, F-UF w/ 1/2" pebbles			
9.3	12.0	Sand, M-coarse w/ 1" pebbles			
12.0	14.3	Dark br. Silty clay grading to gravel			
14.3	24.3	gravel grading to 1.5" pebbles			
24.3	28.0	5" w/ sand			
28.0	31.0	beige clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/2/90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 102 This Water Well Record was completed on (mo/day/yr) 3/23/90 under the business name of Layne Western Co. Inc. by (signature) [Signature]