CORRECTION(S) TO WATER WELL RECORD (WWC-5)
(to rectify lacking or incorrect information)
County: Fond
Location listed as: Location changed to:
Section-Township-Range: 26-T265-R21W 36-T265-R25W
Fraction ( 1/4 1/4 1/4): SE NW SE NE NE NW NE
Other changes: Initial statements: Sevenal Monitoring wells located in rural Fond Country
were clearly in wrong location
Changed to: Moved to Dodge City to match existing set of Safety Kleen
wells.
Comments: Numbers of wells mis-located matched series located in town
verification method:
initials: DAH date: Apr 27, 2007

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726 to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

				TER WELL RECORD	Form WWC-5		-1212 MW 6A		5138A	
LOCATION County:	- 1	R WELL:	Fraction	1/4 NW 1/4 5	Sec 1/4	tion Number	Township Numbe		Range Number	
		rom nearest tov		address of well if loca		- 0		<u> </u>	, - / EQ	
			•		•					
WATER W	ELL OWN	ER: 54/-	TY KLEE	en Corp						
R#, St. Add	ress, Box	# : フフフ	BISTI	nger Rd			Board of Agricu	Iture, Divis	on of Water Resourc	
ity, State, ZI		ELg	IN FLI	60123			Application Nun	nber:		
LOCATE W	ELL'S LO	CATION WITH	4 DEPTH OF	COMPLETED WELL.	33	. ft. ELEVA	TION:			
AN X IN	SECTION N	BUX:					2			
	!	!					face measured on mo/o			
,	wl-	- NE		·			fter hou			
	ī						fter hou			
* w	! !	E		•			and			
-	1	$\vee$		TO BE USED AS:	5 Public wate	, , ,	8 Air conditioning		tion well	
	sw	\SE	1 Domest 2 Irrigatio		6 Oil field wat	er supply	9 Dewatering 10 Donitoring well	12 Othe	r (Specify below)	
i	!	! !	•				esNo			
,	<del>'                                    </del>		mitted	arbacteriological sampi	le submitted to De		ter Well Disinfected? Y			
TYPE OF I	BLANK CA	ASING USED:	milea	5 Wrought iron	8 Concre				Clamped	
1 Steel		3 RMP (S	R)	6 Asbestos-Cemer		(specify below				
PVC		4 ABS	,	<b>7</b> 7 Fiberglass						
	diameter .	4	in, to	ft., Dia			ft., Dia	in. t	o f	
			2. <del>/</del> /	in., weight <b>5</b>	40	lbs./	ft. Wall thickness or ga	uge No		
		PERFORATIO			7 PV	С	10 Asbestos	s-cement	,	
1 Steel		3 Stainles	s steel	5 Fiberglass	8 RM	P (SR)	11 Other (sp	pecify)		
2 Brass		4 Galvaniz	zed steel	6 Concrete tile	9 AB	S	12 None us	ed (open h	ole)	
CREEN OR	PERFOR	ATION OPENIN	IGS ARE:	5 Ga	uzed wrapped		8 Saw cut	11	None (open hole)	
1 Contin	uous slot	3 M	lill slot		re wrapped		9 Drilled holes			
2 Louve	red shutte	r 4 K	ey punched	13 7 Tol	rch cut 33		10 Other (specify)			
SCREEN-PER	RFORATE	) INTERVALS:	_	<del>f</del> . <del></del> ft. to		ft., Fro	m			
00.	VEL 540		From	ft. to	3.3	ft., Fro	m	, ft. to	1	
GRA	WEL PAC	K INTERVALS:								
GROUT M	ATERIAI ·	1 Neat	From	ft. to	Bento	ft., Fro	m Other			
,			ft to	ft., From	9 ft	1/	ft., From			
		rce of possible					tock pens		oned water well	
1 Septio			ral lines	7 Pit privy				el storage 15 Oil well/Gas well		
2 Sewer lines 5 Cess pool				• •			ertilizer storage 16 Other (specify below) secticide storage SOL PLAT THE			
3 Water	tight sewe	r lines 6 Seep	page pit	9 Feedyard		13 Insec	ticide storage	SOL	ent tout	
Direction from	well?	So	UTL			How ma	ny feet? 50			
FROM	то		LITHOLOG	C LOG	FROM	TO	PLUGG	ING INTE	RVALS	
0	7.5	FIII		Parish.					or no more resultance is the control of the control	
	015	Gray	CLAY							
10,5	33.0	prouv	M-C	>A~V						
		Fridhe Herri								
		7 86 - 7 86 7								
		OFFICE								
		The state of the s					WINDOWS MARKET AND A STATE OF THE STATE OF T			
			4.4							
									-	
						4 - 1 a. 100 to	A MA Miles			
			1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1							
				7.78						
CONTRAC	TOR'S O	R LANDOWNE	R'S CERTIFICA	ATION: This water well	was Construe	cted, (2) reco	onstructed, or (3) plugge	ed under n	ny jurisdiction and wa	
completed on		,	2-4-9D				rd is true to the best of			
Vater Well C		•	416		Well Record wa			21-9/	- 	
			acen Co	NOUHANTS		by (signa		n Ke	t-	
		•					e the correct answers. Send to			