CORRECTION(S) TO WATER WELL RECORD (WWC-5)
(to rectify lacking or incorrect information)
County: Fond
Location listed as: Location changed to:
Section-Township-Range: 26-T265-R21W 36-T265-R25W
Fraction (1/4 1/4 1/4): SE NW SE NE NE NW NE
Other changes: Initial statements: Sevenal Monitoring wells located in rural Fond Country
were clearly in wrong location
Changed to: Moved to Dodge City to match existing set of Safety Kleen
wells.
Comments: Numbers of wells mis-located matched series located in town
verification method:
initials: DAH date: Apr 27, 2007

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726 to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

			WATI	ER WELL RECOR	D Form V	VWC-5	KSA 82a	-1212 M	w8	50	903	7/3	8	
1 LOCATION OF WATER WELL:			Fraction		<i>-</i> 1		ion Number	Tov	vnship Nur	nber	R	ange Nur		
County: FC				4 NW 1/4	SE 1/4		76	T	27	S	R	2	E(W)	
Distance and	direction	from nearest tov	vn or city street	address of well if I	located within	city?								
RR#, St. Add City, State, Z	IP Code	# 57 EZ	7 Big 7		123			A	pplication I	Number:			Resources	
AN "X" IN	SECTION	CATION WITH	_	COMPLETED WEI			. ft. ELEVA							
ī	NW	NE 	WELL'S STATION Puring Est. Yield		I water was I water was n. to	ft. be	ft. at ft. at ft. at ft. at ft., at ft	face mea fter and 8 Air cor 9 Dewate Monito	sured on r	hours p hours p hours p il 11 12	umping . umping . n. to 3 Injection Other (\$	well Specify be	gpm gpm ft.	
-	<u>S</u>		mitted						Disinfected			No X		
1 Steel 2 PVC Blank casing Casing heigh	diameter t above la	ASING USED: 3 RMP (SI 4 ABS	in. to 13	5 Wrought iron 6 Asbestos-Cer 7 Fiberglassft., Dia in., weight	ment 9	in. to	specify below	v) 	ia ickness or	Well Three	ded eaded . in. to . No	+		
		R PERFORATION				7 PV			10 Asbe					
1 Steel		Stainless		5 Fiberglass			` '					ify)		
2 Brass		4 Galvaniz ATION OPENIN		6 Concrete tile		9 ABS	•	8 Saw	12 None	usea (o		ne (open	hole)	
	nuous slot		ill slot	_	Gauzed wrap Wire wrappe	•			d holes		11 140	ne (open	noie)	
	ered shutte		ey punched	\sim	Torch cut				r (specify)					
		ED INTERVALS:	From From From	3.3ft.	to		ft., Fror ft., Fror ft., Fror ft., Fror	n n		ft.	to to			
6 GROUT N	MATERIAL:	1 Neat o		②Cement grout	~~	Bentor		•						
Grout Interva		n		ft., From .	. 7 <i>.</i>	ft. t	io //	ft.,	From					
		urce of possible					10 Livestock pens			14 Abandoned water well				
1 Septic tank 4 Lateral lin				7 Pit priv	-		11 Fuel storage			15 Oil well/Gas well				
2 Sewer lines 5 Cess poo			•	8 Sewag		12 Fertilizer storage13 Insecticide storage			16 Other (specify below)					
3 Watertight sewer lines 6 Seepage Direction from well?			_j- ·	9 Feedy	aro	How many feet			801					
FROM	TO	2001	LITHOLOGIC	LOG	FF	юм Т	TO TO	ly leet?	PLL	IGGING	INTERV	ALS		
0	9	CINDE												
9	14/	Brown					W-A		manufacture and a contract of contract of the					
14	23	Med	SAND											
23	3.5		2 SANS	7										
									THE PERSON NAMED IN COLUMN TWO					
		7 19 1 AMILLEPE B												
													· · ·	
						i								
completed or Water Well C	n (mo/day/s	year) /. s License No	1-17-90	TION: This water w	<i></i>		and this reco s completed (rd is true on (mo/da	to the bes					
under the bu	siness nar	ne of Rrrad	con Longu	ILTANIS	Di	- 1- 1	by (signat	ture) 2	1	////		7	odma-t	