CORRECTION(S) TO WATER WELL RE	CORD (WWC-5)
(to rectify lacking or incorrect infor	mation)
	County: Fond
Location listed as:	ocation changed to:
Section-Township-Range: 35-T275-R25 W	35-T265- R25W
Fraction ( 1/4 1/4 1/4): SE NW SE	SE NW SE
Other changes: Initial statements: Sevenal monitoring wel	ls in Dodge City wine
mis-located 6 miles South	
Changed to: T265	
Comments:	
·	
verification method: WWC5 dutabase and mapq	uest website
	initials: DAH date: June 9 2005
submitted by: Vanges Coolerial Summer Data Days III	,
submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant	Ave., Lawrence, KS 66047-3726
to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, St	inte 420, Topeka, KS 66612-1367.

			WELL RECORD	Form WWC-5	KSA 82a-	1212	
<del></del>	OF WATER WELL:	Fraction			tion Number	Township Number	Range Number
County: Fo	ord	SE 1/4	NW 1/4	SE 1/4	35	T 27 🔇	R 25 EW
	direction from nearest town	•		ed within city?		50005470	
	of 603 South 2nd, Do					50885170	<u>MW-5</u>
	ELL OWNER: Fina 011		Company				
	ress, Box # : P. 0. Box					Board of Agriculture,	Division of Water Resources
City, State, ZIP Code : Dallas, TX 75221						Application Number:	
I LOCATE W	/ELL'S LOCATION WITH 4	Depth(s) Groundw	ater Encountered	1 17.5	ft. 2.		3
Mile		Pump st. Yield . N/A	test data: Well wa gpm: Well wa er9.8in. to	ter was ter was	ft. aft. aft. aft. aft. aft. aft. aft. a	ter hours p ter hours p and i B Air conditioning 11 9 Dewatering 12	
	!   !	~					s, mo/day/yr sample was sub-
<u> </u>		vas a chemica/ba nitted	icteriological sample	Submitted to Di	•	er Well Disinfected? Yes	
S TYPE OF	BLANK CASING USED:		E Wrought iron	8 Concre			No ed Clamped
1 Steel	3 RMP (SR)		5 Wrought iron				
(2)PVC	4 ABS		6 Asbestos-Cement		(specify below		ded
	· · · <del>- •</del>		7 Fiberglass				eadedX
							in. to ft.
			n., weight				No. Schedule 40
	REEN OR PERFORATION	_	_	<b>7</b> )PV		10 Asbestos-cem	ı
1 Steel	3 Stainless s		5 Fiberglass		P (SR)		<i>(</i> )
2 Brass			6 Concrete tile	9 AB	S	12 None used (o	pen hole)
SCREEN OR	PERFORATION OPENING		5 Gau	zed wrapped		8 Saw cut	11 None (open hole)
1 Contin	nuous slot 3Mill	slot	6 Wire	wrapped		9 Drilled holes	
2 Louve	red shutter 4 Key	punched	7 Toro				
SCREEN-PER	RFORATED INTERVALS:	From 12	ft. to .	27	ft., From	1 ft.	toft.
							toft.
GR/	VEL PACK INTERVALS:						toft.
		From	ft. to		ft., From		to ft.
6 GROUT M	ATERIAL: 1 Neat ce		Cement grout	(3)Bento			
_		to 7.5	ft From 7				ft. to ft.
	earest source of possible of				10 Livesto		Abandoned water well
1 Septio	•	•	7 Pit privy		_	storage 15	
2 Sewer					_		
	<b>-</b>		8 Sewage la	goon		•	Other (specify below)
	tight sewer lines 6 Seepag	ge bit	9 Feedyard				
Direction from FROM	well? W	LITHOLOGIC L	00	FROM	How man		INTERVALS
	2.5 Brown Sandy		<u>od</u>	FROIVI	TO	1 Lodding	
0							
2.5	5 Tan Fine San						
5		ne to Coarse	Sanu				
14	21 Dark Gray Co		······································				
21	23 Brown Sandy	•	<del></del>				
23	27 Brown Fine S	and					
			*				
7 CONTRAC	TOR'S OR LANDOWNER'S	S CERTIFICATIO	N: This water well	was(1))constru	cted. (2) recor	astructed, or (3) plugged ur	nder my jurisdiction and was
completed on	(mo/dav/year)	01/11/89	water well	337,317	and this recor	d is true to the best of my k	nowledge and belief. Kansas
	ontractor's License No						43
under the bus			sultants, Inc.	TON THOUSING WA			<i>9)[[</i> ][]
winder the bus		161   41.000 1.000					
INCTOLOT	ONS: Use typewriter or ball point per			Diagon ## != ! ! .	by (signati		Which