CORRECTION(S) TO WATER WE	LL RECORD (WWC-5)
(to rectify lacking or incorrec	et information)
Location listed as:	NW SE SE NW SE Several monitoring wells in Dodge City were miles South
Section-Township-Range: 35-T275-K25W	35-T265-R25W
Fraction (1/4 1/4 1/4): SE NW SE	SE NW SE
Other changes: Initial statements: Sevenal monitoring	wells in Dodge City were
mis-located 6 miles South	
Changed to: T 265	
Comments:	
verification method: WWC5 database a	nd Map Quest website
	V

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726 to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

· · · · · · · · · · · · · · · · · · ·		WATER WELL RECORD	Form WWC-5		1212		
LOCATION OF WA	TER WELL: Fr	action	1	ction Number	Township Numbe	_	_
County: Ford		SE 1/4 NW 1/4	SE 1/4	35	T 27 (S) R 25 E	<u>(W</u> _
		ty street address of well if locat	eu within city?		E000F170	MLI O	
WATER WELL OV	South 2nd Street,				50885170	MW-2	
,		d Chemical Company					
RR#, St. Address, Bo					•	Iture, Division of Water Reso	ource
City, State, ZIP Code			20		Application Nun		
AN "X" IN SECTIO		PTH OF COMPLETED WELL s) Groundwater Encountered					
: !	I WELL'	S STATIC WATER LEVEL 1	8•0 ft. b	elow land surf	ace measured on mo/o	day/yr09/29/89	
	NE	Pump test data: Well wa	ter was	ft. af	ter hou	urs pumping	gpm
1 1 1 1 1 1	Est. Yi	eld <mark>N/A</mark> gpm: Well wa	ter was	ft. af	ter hou	urs pumping	gpm
<u>•</u> w 1 1 1	l Bore ⊢	lole Diameter9in. to	30	ft., ε	ınd	in. to	ft.
Ē " !	! WELL	WATER TO BE USED AS:	5 Public water			11 Injection well	
sw	X SE 1	Domestic 3 Feedlot				12 Other (Specify below)	
	1 ' 1 1	Irrigation 4 Industrial				,	
	I Was a	chemical/bacteriological sample	submitted to D			_ · · · · · · · · · · · · · · · · · · ·	ıs sut
, 	§ mitted			Wat	er Well Disinfected? Y	<u>'es</u> (No)	
TYPE OF BLANK		5 Wrought iron				Glued Clamped	
1 Steel	3 RMP (SR)	6 Asbestos-Cement		(specify below		Welded	
@PVC	4 ABS	7 Fiberglass				Threaded X	
		. 8, 5 ft., Dia					
Casing height above	and surface	in., weight			t. Wall thickness or ga	uge No. "Schedule .40	
TYPE OF SCREEN C	R PERFORATION MATE	· · · · · - ·	(7) PV		10 Asbestos	s-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RM	MP (SR)	11 Other (sp	pecify)	
2 Brass	4 Galvanized stee		9 AB	_		ed (open hole)	
SCREEN OR PERFO	RATION OPENINGS AR	E: 5 Gau	zed wrapped		8 Saw cut	11 None (open hole)	<i>i</i>)
1 Continuous sle			wrapped		9 Drilled holes		
2 Louvered shut							
SCREEN-PERFORAT		m 8 • 5 ft. to .					
		m ft. to .					
GRAVEL PA		m 7 ft. to .					
	Fro						
GROUT MATERIA			(3)Bento	onite 4	Other		
		5 ft., From	. ? ft.				ft.
	ource of possible contam			10 Livest		14 Abandoned water well	
1 Septic tank	4 Lateral lines	7 Pit privy		(1) Fuel s	storage		
2 Sewer lines	5 Cess pool	8 Sewage la	goon		zer storage	16 Other (specify below)	
•	ver lines 6 Seepage pit	9 Feedyard			<u> </u>		• • • •
Direction from well? FROM TO	SE TOTAL	HOLOGIC LOG	FROM	How man		ING INTERVALS	
0 10	Brown to Tan Fine		FROM	10	1 2000	IIING INTERVALS	
10 12.5	Gray Coarse Sand	Sanu					
12.5 13.5	1	27 av		 			
13.5 20.5	Brown Sandy Lean (*		†			
	Gray Medium to Coa						
	Gray-Brown Fine to						
26 30	Brown Sandy Lean (Ji ay.		 			
				+			
				+			
		*					
				 			
			-	 			
				.			
	OR LANDOWNER'S CEI	RTIFICATION: This water well v	was ((1)) constru	icted, (2) reco	nstructed, or (3) plugge	ed under my jurisdiction and	aw t
ompleted on (mo/day		/11/89					ansas
	's License No 41!		Well Record wa		///		
inder the business na		rracon Consultants, Inc.		by (signat		///has	
INICTOLICTIONIC III	honorestar or hall maint man. Of Ci	ISE PRESS FIRMLY and PRINT clearly.	Please fill in blanks	underline or circle	the correct answers send tor	CALLERY VICTOR DONORTHON	