## 

verification method: Written description on this record and on plugging report, city street map, and mapping tool on KGS

\_\_\_\_\_\_initials: DRL date: 3/4/2010

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726 to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

Comments:

		W	ATER WELL REC	ORD Form WWC-5	KSA 82a-1	1212 ID No		MW	16
1 LOCAT	ION OF WA	TER WELL:	Fraction	OND TOM WWO-5		tion Number	Township Num	ber Range Number	er
County: {				SE 1/2 SW		27	T Ale	% <b>~</b>	EM)
		from nearest to	wn or city street a	ddress of well if located Wyatt Ear	within city?		. kc		
2 WATER	R WELL OW	NER: THE K	MISKET COM	PORPTION (M	ICH AEL	KEY)	1 00		
RR#, St. A City, State,	ddress, Box ZIP Code	# : P.D.B	on 26210	. NR 73126		,	Application Nu		ources
3 LOCATE	WELL'S LC	CATION WITH	4 DEPTH OF C	OMPLETED WELL	<b>5</b> 5.0	ft. ELEVAT	TION: 2496.	00	
AN "X" II	N SECTION N - NW		Depth(s) Groun WELL'S STATIO Pur Est. Yield WELL WATER 1 Domestic 2 Irrigation	dwater Encountered C WATER LEVEL	75.0 3ft. below respectively. The second r	ft. w land surfaceft. aft. aft. a upply supply rn & garden)	2e measured on mo/da after	hours pumping hours pumping 11 Injection well 12 Other (Specify below)	gpm gpm
	<b>5</b>	1	mitted	rbacteriological sample	submitted to t	•	ater Well Disinfected?		is sub-
		CASING USED:		5 Wrought iron	8 Concre			S: Glued Clamped	
1 Stee	3	3 RMP (S 4 ABS	,	<ul><li>6 Asbestos-Cement</li><li>7 Fiberglass</li></ul>				Welded Threaded	
Blank casi	ng diameter	2	in. to					in. to	
Casing hei	ght above la	and surface	-3.34	in., weight			lbs./ft. Wall thickness	or guage No. Sch. 40 f	PVC.
TYPE OF	SCREEN O	R PERFORATIO			Q PV			tos-Cement	
1 Stee		<ol> <li>Stainles</li> <li>Galvania</li> </ol>		5 Fiberglass 8 RMP (SR) 6 Concrete tile 9 ABS			11 Other (Specify)		
2 Bras						3		, ,	
SCREEN OR PERFORATION OPENINGS ARE:  1 Continuous slot (3 Mill slot)				5 Guazed wrapped 6 Wire wrapped			8 Saw cut 9 Drilled holes	11 None (open hole	e)
	itinuous slot vered shutte		ey punched	7 Torch					ft.
		ED INTERVALS	, ,	25 # 10	55	ft From	· · · · · · · · · · · · · · · · · · ·	ft. to	
SUNEEIN-I	FERFORAT	EDINIERVALO							
(	GRAVEL PA	CK INTERVALS	8: From	<b>7.3</b> ft. to	<i>55</i>	ft., From		ft. to ft. to	ft.
			From	ft. to		ft., From		ft. to	ft.
6 GROU	JT MATERIA	u 1 Nea	at cement _	_ 2 Cement grout	5 Bent	onite) 4	Other		
Grout Inter						) )	ft From	ft. to	ft
			contamination:			10 Livest		14 Abandoned water well	
	otic tank	•	ral lines	7 Pit privy		11 Fuel storage		15 Oil well/Gas well	
2 Sewer lines 5 Cess pool				8 Sewage lagoon		· ·		16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit				9 Feedyard		13 Insecticide storage		Just Site	
Direction from well?						How man	y feet?		
FROM	ТО		LITHOLOGIC	LOG	FROM	TO	PLUGO	GING INTERVALS	
$\circ$	1	Top Soi	1						
	23		sitty, dry					****	
23	30	Sand.	very fine	tofine					
30	36	Sand	+ grave						
360	47	Clay, o	Silty, mo	ist					
47	55	Sand, Fir	re tocicarse,	6 "Clay Layer at	52'				
			<u> </u>						
	-								
y#/###									
7									
Water Well	ACTOR'S Con (mo/day/y Contractor's Jusiness nan	Licence No	er's certifica 201200 594 20 Great	This Water	well Record	was completed	nstructed, or (3) plug cord is true to the best d on (mo/day/yr) O signature)	ged under my jurisdiction ar of my knowledge and belief. R 911712003	id was (ansas
		<u> </u>			e fill in blanks. und			ree copies to Kansas Department of H	lealth
and Enviro	onment, Bureau		ection, 1000 SW Jackso					ELL OWNER and retain one for your	-Sunii