1 LOCATION OF WATER WELL: Fraction Fraction Frord NW
WATER WELL OWNER: River Stop Tag 00249706
Tag 00249706 Sort River Stop Tag 00249706 Sort Address, Box # 705 S. 14th St St Address, Box # 705 S. 14th St St Address, Box # 705 S. 14th St St Address, Box # 705 S. 14th
RR#, St. Address, Box # 705 S. 14th St Dodge City, Ks Dodge City, Ks Application Number:
RR#, St. Address, Box # : 705 S. 14th St State, ZIP Code Dodge City, Ks Dodge City, Ks Application Number
City State ZIP Code
3 LOCATE WELL'S LOCATON WITH 4 NA NY IN SECTION BOX: N
WELL'S STATIC WATER LEVEL 31.45 ft. below land surface measured on mol/day/yr Pump test data: Well water was ft. after hours pumping gpm gpm gpm y w w y y y y y y y y y y y y y y y y y
WELL'S STATIC WATER LEVEL 31.45 ft. below land surface measured on mol/day/yr Pump test data: Well water was ft. after hours pumping gpm gpm gpm gpm well water was ft. after hours pumping gpm
WELL'S STATIC WATER LEVEL 31.45 ft. below land surface measured on mol/day/yr Pump test data: Well water was ft. after hours pumping gpm gpm gpm gpm well water was ft. after hours pumping gpm
Pump test data: Well water was ft. after hours pumping gpm gpm Well water was ft. after hours pumping gpm gpm Well water was ft. after hours pumping gpm gpm Well water was ft. after hours pumping gpm gpm Well water was ft. after hours pumping gpm gpm water was ft. after hours pumping gpm gpm gpm gpm was gpm water water well plaintened water supply a Sair conditioning 11 Injection well submitted to Department? Yes No X if yes, mo/daylyr sample was submitted water supply as a chemical/bacteriological sample submitted to Department? Yes No X if yes, mo/daylyr sample was submitted water well Disinfected? Yes No X if yes, mo/daylyr sample was submitted water well Disinfected? Yes No X if yes, mo/daylyr sample was submitted water well Disinfected? Yes No X if yes, mo/daylyr sample was submitted water well Disinfected? Yes No X if yes, mo/daylyr sample was submitted water well Disinfected? Yes No X if yes, mo/daylyr sample was submitted water well Disinfected? Yes No X if yes, mo/daylyr sample was submitted water well Disinfected? Yes No X if yes, mo/daylyr sample was submitted to Department? Yes No X if yes, mo/daylyr sample was submitted water well Disinfected? Yes No X if yes, mo/daylyr sample was submitted to Department? Yes No X if yes, mo/daylyr sample was submitted water well Disinfected? Yes No X if yes, mo/daylyr sample was submitted to Department? Yes No X if yes, mo/daylyr sample was submitted to Department? Yes No X if yes, mo/daylyr sample was submitted to Department? Yes No X if yes, mo/daylyr sample was submitted to Department? Yes No X if yes, mo/daylyr sample was submitted to Department? Yes No X if yes, mo/daylyr sample was submitted to Department? Yes No X if yes, mo/daylyr sample was submitted to Department? Yes No X if yes, mo/daylyr sample was submitted to Department? Yes No X if yes, mo/daylyr sample was submitted to Department? Yes No X if yes, mo/daylyr sample was submitted to Department? Yes No X if yes, mo/daylyr sample was submitted to Department? Yes No X if yes, mo/daylyr sample was submi
Est. Yield gpm: Well water was ft. after hours pumping gpm well water was ft. after hours pumping gpm ft. and in. to ft. by the provided by the provided ft. and in. to ft. by the provided ft.
Bore Hole Diameter 8 in. to 50 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 9 Dewatering 12 Other (Specify below) Variable Vari
Bore Hole Diameter 8 in. 10 50 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 9 Dewatering 12 Other (Specify below) Variable Vari
2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X 5 TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded X Blank casing diameter 2 in. to 15 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 0 in., weight 716 lbs./ft. Wall thickness or gauge No. 154 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 15 ft. to 50 ft. From ft. to ft. From 13 ft. to 38 ft. From ft. to ft. From 13 ft. to 38 ft. From ft. to ft. From 13 ft. to 38 ft. From ft. to ft. From 1 ft. to ft. From 1 ft. to ft. From ft.
2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X 5 TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded X Blank casing diameter 2 in. to 15 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 0 in., weight 716 lbs./ft. Wall thickness or gauge No. 154 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 15 ft. to 50 ft. From ft. to ft. From 13 ft. to 38 ft. From ft. to ft. From 13 ft. to 38 ft. From ft. to ft. From 13 ft. to 38 ft. From ft. to ft. From 1 ft. to ft. From 1 ft. to ft. From ft.
2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X 5 TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded X Blank casing diameter 2 in. to 15 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 0 in., weight 716 bbs./ft. Wall thickness or gauge No. 154 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 15 ft. to 50 ft. From ft. to ft. From 13 ft. to 38 ft. From ft. to ft. From 13 ft. to 38 ft. From ft. to ft. From 13 ft. to 38 ft. From ft. to ft. From 15 ft. to ft. From ft. to ft.
S
Substitute
Type OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped
Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
2 PVC
Blank casing diameter 2
Casing height above land surface 0 in., weight .716 lbs./ft. Wall thickness or gauge No154 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 15 ft. to 50 ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 38 ft. to 50 ft. From ft. to ft. From 13 ft. to 38 ft. From ft. to ft. GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals From 1 ft. to 13 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 15 ft. to 50 ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 38 ft. to 50 ft. From ft. to ft. From 13 ft. to 38 ft. From ft. to ft. GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals From 1 ft. to 13 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 15 ft. to 50 ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 38 ft. to 50 ft. From ft. to ft. From 13 ft. to 38 ft. From ft. to ft. GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals From 1 ft. to 13 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
2 Brass
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 15 ft. to 50 ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 38 ft. to 50 ft. From ft. to ft. From ft. From ft. To ft. From ft. Fro
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 15 ft. to 50 ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 38 ft. to 50 ft. From ft. to ft. From 13 ft. to 38 ft. From ft. to ft. GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals From 1 ft. to 13 ft. From ft. to ft. What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
SCREEN-PERFORATED INTERVALS: From 15 ft. to 5U ft. From ft. to ft. to ft. ft. o ft. o ft. ft. o
From GRAVEL PACK INTERVALS: From From From St. to 50 ft. From ft. From ft. to ft. From ft. to ft. From ft.
GRAVEL PACK INTERVALS: From fr. to 38 ft. to 50 ft. From ft. to ft. From ft. to ft. o ft. o ft. ft. o ft. o </td
From 13 ft. to 38 ft. From ft. to ft. to ft. ft. o
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals From 1 ft. to 13 ft. From ft. to ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
Grout Intervals From 1 ft. to 13 ft. From ft. to ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
F
4.0
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/ Gas well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage CONTAMINATED SITE
Direction from well? How many feet?
FROM TO CODE LITHOLOGIC LOG FROM TO PLUGGING INTERVALS
0 8 Clay, sandy
8 24 Sand, fine to coarse grained,
Poorly sorted
24 35 Clay, silty
35 38 Sandy, dense clay
38 41 Very fine grained, clayey sand
41 43 Sandy, plastic clay
43 50 Very fine grained sand, clayey,
w/clay strks, thin
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was
Water Well Contractor's License No. 554 This Water Well Record was completed on (mo/day/yr) 2-17-06
under the business name of Woofter Pump & Well Inc. by (signature)
INSTRUCTIONS: Please fill in blanks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, 1000 SW Jackson St., Ste. 420, Topeka, Kansas 66612-1367. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.