

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County:		$\frac{1}{4}$ $\frac{1}{4}$ SE $\frac{1}{4}$	27	T 26 S	R 25 E
Distance and direction from nearest town or city street address of well if located within city? 2412 Park St					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		Application Number:			
City, State, ZIP Code :		Dodge City, KS 67801			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 16.5 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1.5 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 3.5 ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 9.78 in. to 16.5 in. to ft.			
		WELL WATER TO BE USED AS:			
		<input checked="" type="checkbox"/> Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		<input type="checkbox"/> Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes <input checked="" type="checkbox"/> No <input checked="" type="checkbox"/> If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>			
5 TYPE OF BLANK CASING USED:		5 Wrought iron		8 Concrete tile	
1 Steel		3 RMP (SR)		CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped	
<input checked="" type="checkbox"/> PVC		4 ABS		Welded	
Blank casing diameter 5 in. to 13.3 in. to ft. Dia		6 Asbestos-Cement		Threaded	
Casing height above land surface 12 in. weight 2.00 lbs./ft. Wall thickness or gauge No.		7 Fiberglass			
TYPE OF SCREEN OR PERFORATION MATERIAL:		10 Asbestos-cement			
1 Steel		3 Stainless steel		11 Other (specify)	
2 Brass		4 Galvanized steel		12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped		8 Saw cut	
1 Continuous slot		6 Wire wrapped		11 None (open hole)	
2 Louvered shutter		7 Torch cut		9 Drilled holes	
3 Mill slot		10 Other (specify)			
4 Key punched					
SCREEN-PERFORATED INTERVALS:		From 133 ft. to 165 ft.		From ft. to ft.	
		From ft. to ft.		From ft. to ft.	
GRAVEL PACK INTERVALS:		From 145 ft. to 165 ft.		From ft. to ft.	
		From ft. to ft.		From ft. to ft.	
6 GROUT MATERIAL:		1 Neat cement		2 Cement grout	
Grout Intervals: From 4 ft. to 25 ft.		3 Bentonite		4 Other	
What is the nearest source of possible contamination:		10 Livestock pens		14 Abandoned water well	
<input checked="" type="checkbox"/> Septic tank		11 Fuel storage		15 Oil well/Gas well	
2 Sewer lines		12 Fertilizer storage		16 Other (specify below)	
3 Watertight sewer lines		13 Insecticide storage			
4 Lateral lines		How many feet? 50 ft Plus			
5 Cess pool					
6 Seepage pit					
7 Pit privy					
8 Sewage lagoon					
9 Feedyard					
Direction from well? South					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	6	Top Soil	103	106	Fine to med Sand & gravel
6	20	Coarse gravel	106	115	gray & Brown clay
20	25	Sand & gravel (loose)	115	165	Fine to med Sand & gravel
25	52	Brown clay	165-170		Blue Shale
52	55	Fine to med Sand & gravel			
55	60	Brown clay			
60	62	Hard Rock			
62	66	Brown Sandy clay			
66	70	Fine to med Sand & gravel			
70	80	Brown Sandy clay			
80	83	Hard Rock			
83	86	Fine to med Sand & gravel			
86	90	Brown Sandy clay			
90	100	Fine to med Sand & gravel			
100	103	Hard Rock			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-4-04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 172 This Water Well Record was completed on (mo/day/yr) 8-13-04 under the business name of Tanagan Drilling by (signature) me					