

1 LOCATION OF WATER WELL: County: Ford	Fraction SW 1/4 NE 1/4 NE 1/4	Section Number 35	Township Number T 26 S	Range Number R 25 E/W
--	---	-----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city? **In Wright Park, south side of Dodge City**
~~Approximately 1/4 mile south and 1/4 mile west of Dodge City~~

2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :	City of Dodge City P.O. Box 880 Dodge City, KS 67801-0880	Board of Agriculture, Division of Water Resources Application Number:
---	--	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 161 ft. ELEVATION: unknown
--	---

Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL **14.78** ft. below land surface measured on **mo/day/yr 2-20-98**

Pump test data: Well water was **not ch'd** ft. after hours pumping gpm

Est. Yield **unknown** gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter **8** in. to **165** ft., and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 <u>PVC</u>	4 ABS	7 Fiberglass	Welded
Blank casing diameter 5 in. to 149 ft., Dia in. to ft., Dia in. to ft.			Threaded
Casing height above land surface 24 in., weight 2.36 lbs./ft. Wall thickness or gauge No. 214			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 <u>PVC</u>	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 <u>Mill slot</u>	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 149 ft. to 159 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 144 ft. to 165 ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other <u>Bentonite Holeplug</u>
Grout Intervals: From ft. to ft., From ft. to ft., From ft. to 144 ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	<u>None known</u>
Direction from well?	How many feet?			

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Topsoil			
2	10	Clay, gray			
10	23	Sand and gravel, coarse, medium, fine			
23	54	Clay, tan			
54	71	Sand and gravel, medium, fine			
71	85	Clay, tan			
85	95	Sand and gravel, medium, fine			
95	96	Clay, tan			
96	99	Sand and gravel, medium, fine			
99	107	Clay, tan			
107	160	Sand and gravel, coarse, medium, fine			
160	165	Clay, yellow and gray			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-18-98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/yr) 3-2-98 under the business name of Clarke Well & Equipment, Inc. by (signature) <i>[Signature]</i>

OFFICE USE ONLY

T

R

E/W

SEC.

1/4

1/4

1/4