			m WWC-5		sion of Water				
✓ Original	Record		hange in Well Use		urces App. No		Well ID		
1 LOCATION OF WATER WELL:			Fraction	Section Number Township Number				ge Number	
County			NW ¼ NW ¼ NE ¼						
2 WELL OWNER: Last Name: Brack First: Bud Street or Rural Address where well is located (if unknown, distance and									
Business: direction from nearest town or intersection): If at owner's addr								heck here: 🔽	
Address: 3006 Center Avenue Address:									
City:	Dodge Ci	ty State:	KS ZIP: 67801						
3 LOCAT		• • • • • • • • • • • • • • • • • • • •		055		27 7000	•4		
WITH "		4 DEPTH OF C	COMPLETED WELL:		. 255 ft. 5 Latitude: 37.78661 (decimal degrees)				
Depth(s) Groundwater Encountered: 1)!					ft. Longitude: 100.03681 (decimal degrees)				
2)									
	■					tt. D2/2018 Source for Latitude/Longitude: D2/2018 GPS (unit make/model:)			
			face, measured on (mo-day-	yr) vr)					
			ell water was fi		(WAAS enabled? ☐ Yes ☐ No) ☐ Land Survey ☐ Topographic Map				
			hours pumping						
			ell water was f						
SW	SE		hours pumping	gpm	6 Elevation: 2620ft. ☑ Ground Level ☐ T			I TOC	
		Estimated Yield: .	gpm		6 Elevation:			Level 10C	
			er:10 in. to255					pograpnic Map	
1 n			in. to	ft.		M Other Warding			
7 WELL WATER TO BE USED AS:									
1. Domestic:	- ······ - · · · · · · · · · · · · · ·				10. Oil Field Water Supply: lease				
			fer Recharge: well ID						
	☐ Livestock 8. ☐ Monitoring: well ID								
3. Feedlo					· ·				
4. ☐ Industrial ☐ Recovery				SALIGOT		13. Other (specify):			
Was a chemical/bacteriological sample submitted to KDHE? ☐ Yes ☑ No If yes, date sample was submitted:									
Water well disinfected? ☑ Yes ☐ No 8 TYPE OF CASING USED: ☐ Steel ☑ PVC ☐ Other									
8 TYPE OF CASING USED: Steel M PVC Other CASING JOINTS: M Glued Clamped Welded Threaded									
Casing diameter 5 in to 255 ft., Diameter in to ft., Diameter in to SDR21 Casing height above land surface 12 in Weight Ibs/ft. Wall thickness or gauge No. SDR21									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
☐ Steel ☐ Stainless Steel ☐ Fiberglass ☑ PVC ☐ Other (Specify)									
☐ Brass ☐ Galvanized Steel ☐ Concrete tile ☐ None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
☐ Continuous Slot ☑ Mill Slot ☐ Gauze Wrapped ☐ Torch Cut ☐ Drilled Holes ☐ Other (Specify)									
□ Louvered Shutter □ Key Punched □ Wire Wrapped □ Saw Cut □ None (Open Hole)									
SCREEN-PERFORATED INTERVALS: From 215 ft. to 255 ft., From ft. to ft., From ft. to ft., From ft.									
GRAVEL PACK INTERVALS: From									
9 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☑ Bentonite ☐ Other									
Grout Intervals: From									
		le contamination:							
☐ Septic		☐ Lateral			Livestock Pen		icide Storage		
☐ Sewer		☐ Cess P			Fuel Storage		loned Water V	Well	
☐ Watertight Sewer Lines ☐ Seepage Pit ☐ Feedyard ☐ Fertilizer Storage ☐ Oil Well/Gas Well									
Other (Specify) Direction from well? Distance from well?									
10 FROM	TO TO		DLOGIC LOG	FROM		JTHO, LOG (cont.) o		GINTERVALS	
0		Brown Clay & Calic		212		ellow Clay		- IIIIIII	
83		Sand Rock		- 1-		Onom Olay			
88		Brown Clay		-					
100			Sandrock						
110			Fine Sand & Sandrock Layers						
		Brown Sandy Cla		-					
135 155		Fine Sand	<u>y</u>	Notes:					
		Medium Sand		110163.					
210 212 Brown Clay 11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged									
under my jurisdiction and was completed on (mo-day-year) .05/02/2018 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 533. This Water Well Record was completed on (mo-day-year) 05/23/2018									
under the business name of Jantzen Water Well									
12 11		Send one copy to WAT	ER WELL OWNER and retain	one for your rec	ords. Fee of \$5.0	00 for each constructed w	rell.		
KS Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-3565.									
Visit us at http://www.kdheks.gov/waterwell/index.html KSA 82a-1212									