

WATER WELL RECORD Form WWC-5

Division of Water Resources App. No.

Well ID

- Original Record Correction Change in Well Use

1 LOCATION OF WATER WELL: County: Ford Fraction SW 1/4 NW 1/4 NW 1/4 NW 1/4 Section Number 14 Township Number T 26 S Range Number R 25 E W

2 WELL OWNER: Last Name: First: Street or Rural Address where well is located (if unknown, distance and direction from nearest town or intersection): If at owner's address, check here: Business: Our Lady of Guadalupe Address: PO Box 670 City: Dodge City State: KS ZIP: 67801

3 LOCATE WELL WITH 'X' IN SECTION BOX: N W E S 1 mile. 4 DEPTH OF COMPLETED WELL: 260 ft. Depth(s) Groundwater Encountered: 1) 152 ft. 2) ... ft. 3) ... ft., or 4) Dry Well. WELL'S STATIC WATER LEVEL: 152 ft. 5 Latitude: 37.793501 Longitude: -100.033010

7 WELL WATER TO BE USED AS: 1. Domestic: Household Lawn & Garden Livestock Irrigation Feedlot Industrial. 5. Public Water Supply: well ID. 6. Dewatering: how many wells? 7. Aquifer Recharge: well ID. 8. Monitoring: well ID. 9. Environmental Remediation: well ID. 10. Oil Field Water Supply: lease. 11. Test Hole: well ID. 12. Geothermal: how many bores? 13. Other (specify):

Was a chemical/bacteriological sample submitted to KDHE? Yes No If yes, date sample was submitted: Water well disinfected? Yes No

8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded Casing diameter: 6 in. to 260 ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface: 18 in. Weight lbs./ft. Wall thickness or gauge No. SDR 17. TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel PVC Other (Specify) Brass Galvanized Steel None used (open hole). SCREEN OR PERFORATION OPENINGS ARE: Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify) Louvered Shutter Key Punched Wire Wrapped Saw Cut None (Open Hole). SCREEN-PERFORATED INTERVALS: From 160 ft. to 260 ft., From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 0 ft. to 5 ft., From 40 ft. to 260 ft., From ft. to ft.

9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From 5 ft. to 40 ft., From ft. to ft., From ft. to ft. Nearest source of possible contamination: No potential source of contamination within 200 ft. Septic Tank Lateral Lines Pit Privy Livestock Pens Insecticide Storage Sewer Lines Cess Pool Sewage Lagoon Fuel Storage Abandoned Water Well Watertight Sewer Lines Seepage Pit Feedyard Fertilizer Storage Oil Well/Gas Well Other (Specify) Direction from well? West Distance from well? 200 ft.

Table with 6 columns: 10 FROM, TO, LITHOLOGIC LOG, FROM, TO, LITHO. LOG (cont.) or PLUGGING INTERVALS. Includes a Notes section.

11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo-day-year) 12/17/2021 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 846 This Water Well Record was completed on (mo-day-year) 12/28/2021 under the business name of Nash Water Well Service, LLC

Form	WWC5
Contractor	Nash Water Well Service, LLC
Well Owner	
Doc ID	1604207

Lithology

0	20	TOP SOIL
20	60	BROWN TAN CLAY & THIN FINE SAND STREAKS
60	100	TAN CLAY WITH FINE SAND STREAKS WITH WHITE CALICHE WHITE CLAY STREAKS
100	130	FINE COARSE SAND
130	150	FINE MEDIUM SAND TAN CLAY
150	160	FINE COARSE SAND TAN CLAY
160	200	FINE MEDIUM SAND TAN CLAY
200	225	FINE COARSE SAND
225	235	FINE COARSE SAND WITH SMALL TO MEDIUM GRAVEL
235	238	TAN GRAY YELLOW CLAY WITH FINE SAND STREAKS
238	257	FINE SAND TAN YELLOW CLAY & SANDSTONE
257	259	BLUE SHALE
259	265	GRAY CLAY