

[1] LOCATION OF WATER WELL: County: Ford		Fraction NE ¼ SE ¼ SE ¼	Section Number 27	Township Number T 26 S	Range Number R 25 EW
Distance and direction from nearest town or city street address of well if located within city? 1520 West Wyatt Earp, Dodge City, Kansas					
[2] WATER WELL OWNER: Fina Oil and Chemical Company RR#, St. Address, Box # : P.O. Box 2159 City, State, ZIP Code : Dallas, Texas 75221		MW-4 Board of Agriculture, Division of Water Resources Application Number: 01948014			
[3] LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		[4] DEPTH OF COMPLETED WELL. 47 ft. ELEVATION: Approx. 1245'			
		Depth(s) Groundwater Encountered 1. .38 ft. 2. . ft. 3. . ft. WELL'S STATIC WATER LEVEL 39.90 ft. below land surface measured on mo/day/yr 07/01/94 Pump test data: Well water was . ft. after . hours pumping gpm Est. Yield N/A gpm; Well water was . ft. after . hours pumping gpm Bore Hole Diameter . 8.25 in. to . ft., and . in. to . ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only ⑩ Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No... X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X			
[5] TYPE OF BLANK CASING USED:					
1 Steel ② PVC Blank casing diameter . 2 in. to . 33.5 ft., Dia . in. to . ft., Dia . in. to . ft. Casing height above land surface . -3 in., weight lbs./ft. Wall thickness or gauge No. Schedule 40		3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued . Clamped . Welded . Threaded . X			
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter ③ Mill slot 4 Key punched		5 Fiberglass 6 Concrete tile 7 Torch cut 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)			
SCREEN-PERFORATED INTERVALS:					
From . 33.5 ft. to . 48 ft.		From . ft. to . ft.			
GRAVEL PACK INTERVALS:		From . 30 ft. to . 48 ft.			
[6] GROUT MATERIAL:					
Grout Intervals: From . 0 ft. to . 28 ft.		From . 28 ft. to . 30 ft.			
What is the nearest source of possible contamination:					
1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit		7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)			
Direction from well?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0.0	1.0	Concrete and Sand Base			
1.0	7.0	Lean Clay With Silt, Brown			
7.0	13.0	Lean Clay With Silt, Light Brown to Brown, Trace Caliche, Odor			
13.0	23.0	Silty Lean Clay, Light Brown to Tan, Odor			
23.0	34.0	Fine to Very Coarse Sand, Gray to Black, Stain, Odor			
34.0	48.0	Fine to Medium Sand, Gray to Tan, Odor			
[7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ① constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 07/01/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 8/15/94 under the business name of Terracon Consultants, Inc. by (signature)					

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.