				R WELL RECORD F	orm WWC-5	KSA 8	2a-1212			
		TER WELL:	Fraction	CE CE		tion Number	1 '26	\sim	Range Number	
County: I	ora		NE 1/4	SE 1/4 SE	1/4	27	т 26	(s)] R ²⁵ EW	
				ddress of well if located City, Kansas	within city?					
WATER	R WELL OW	NER: Fina	Oil and	Chemical Compan	У		MW-1		01948014	
_ RR#, St. /	Address, Bo	x # : P.O.	Box 2159				Board of A	Agriculture,	Division of Water Resources	
City, State	, ZIP Code	: Dall	as, Texas	75221		Application Number:			A NOTE OF THE PROPERTY OF THE	
LOCATE	E WELL'S L	OCATION WITH 4	DEPTH OF C	OMPLETED WELL	47	ft. ELE\	Appr	ox. 124	5'	
ے AN "X"	IN SECTIO	N BOX:	- Depth(s) Ground	water Encountered 1	38	ft	. 2	ft. 3	3 <u>.</u>	
Ŧ	!	! ^							07/01/94	
-	- NW	NE							imping gpm	
	1		st. Yield !\!/ !	H: gpm: Well water	was	ft.	after	. hours pu	imping gpm	
* w -		E B	Bore Hole Diame						. to	
₹	!				Public wate		8 Air conditioning		Injection well	
-	- SW	SE	1 Domestic				9 Dewatering		Other (Specify below)	
	1	^	2 Irrigation							
Į L		v	Vas a chemical/l	pacteriological sample su	bmitted to De	epartment?	YesNo	; If yes	, mo/day/yr sample was sub	
-		, n	nitted			v	Vater Well Disinfecte	ed? Yes	No X	
5 TYPE C	OF BLANK (CASING USED:		5 Wrought iron	8 Concre	ete tile	CASING JO	INTS: Glue	d Clamped	
1 Ste		3 RMP (SR)		6 Asbestos-Cement	9 Other	(specify bel	ow)	Weld	led	
2PV	/C	4 ABS		_7 Fiberglass				Thre	adedXX	
Blank casi	ng diameter	2ig	1. to 3.2 •	⁵ ft., Dia					in. to ft.	
Casing hei	ight above la	and surface = 3	3	.in., weight		Ib	s./ft. Wall thickness	or gauge N	lo. Schedule 40	
TYPE OF	SCREEN O	R PERFORATION	MATERIAL:		(7)PV	С	10 Asl	estos-ceme	ent	
1 Ste	eel	3 Stainless s	5 Fiberglass	8 RM	IP (SR)	11 Other (specify)				
2 Brass 4 Galvanized steel				6 Concrete tile				12 None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE:				5 Gauzed	5 Gauzed wrapped		8 Saw cut	٠.	11 None (open hole)	
1 Co	ntinuous slo	ot 3Mill	slot	6 Wire w	6 Wire wrapped				(
	uvered shut	•	punched	7 Torch o	ut 47.5		9 Drilled holes 10 Other (specif	v)		
SCREEN-F	PERFORAT	ED INTERVALS:	From 32	•5 ft. to	47.5	ft F			toft.	
			From	ft. to					toft.	
c	BRAVEL PA	CK INTERVALS:	From 30	•5 ft to	47.5	ft F	rom	ft . 1	toft.	
			From	ft. to		ft., F				
6 GROUT	MATERIAL	.: 1) Neat ce			(3)Bento					
Grout Inter		mft	28.	2 Cement grout 5 ft., From 28.	5 6 ft	30.	ft From			
		ource of possible co					estock pens		bandoned water well	
		•		7 Dit priva				storage 15 Oil well/Gas well		
1 Septic tank 4 Lateral lines 2 Sewer lines 5 Cess pool							•			
2 Sewer lines 5 Cess pool 3 Watertight sewer lines 6 Seepage pit				8 Sewage lagoo	n		tilizer storage			
	-	rei lines o Seepaç	ge pit	9 Feedyard			cticide storage			
Direction f FROM	TO TO	Ι	LITHOLOGIC	106	FROM	TO TO	nany feet?	LIGGING I	NTERVALS	
0.0	0.5	Sand and Gr		LOG	FROIVI	10	, ,	-oddiiva i	IVILITYALO	
0.5	4.5	Sandy Lean		to Prorm						
4.5	23.0						THE PERSON NAMED IN THE PE			
				, Trace Caliche						
23.0	28.0		Black to	Gray, Stain,	the course accompany and a second					
20. 2	25.0	Odor							· · · · · · · · · · · · · · · · · · ·	
28.0	35.0	rine to Ver	y Coarse S	Sand, Black to						
25.0	20.0	Gray, Stain		1 -1 -						
35.0	38.0			nd, Black to						
00.		Gray, Stain								
38.0	48.0			Brown to Tan,						
		Trace Coars	e Sand							
			-							
7 CONTE	BACTOR'S	OR LANDOWNER'S	S CERTIFICATI	ON: This water well was	(1) constru	oted (2) re	constructed or (2)	aluqqed us	der my jurisdiction and was	
Completed	on (mo/dev	(vear) 07/	01/94	Ort. This water well was	Constru	and this se	constructed, Of (3)	set of my les	gwledge and belief: Kansas	
				This Water Wel						
				ltants, Inc.	necora wa	-		1	7	
uriuer the	pusiness na	ule of TETTO	con consu.	realies, IIIC.		by (sign	nature)	ww	/ Main	