

1	LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
	County: Ford	SE ¼ SE ¼ NE ¼	35	T 26 S	R 25 NW

Distance and direction from nearest town or city street address of well if located within city?

75' South of the SW corner of Hazel Ave & Sunnyside St.

2	WATER WELL OWNER:	Robert Rostetter	
	RR#, St. Address, Box # :	302 South Second St.	Board of Agriculture, Division of Water Resources
	City, State, ZIP Code :	Dodge City, Kansas	Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

NW	NE
SW	SE

4 DEPTH OF COMPLETED WELL: 32 ft. ELEVATION: 25 ft.

Depth(s) Groundwater Encountered 1. 25 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 25.62 ft. below land surface measured on mo/day/yr

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 7.5/8 in. to 32 ft., and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Lawn and garden only
		10 Monitoring well

9 Dewatering

12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
		7 Fiberglass		Threaded. X

Blank casing diameter 2 . . . in. to . . . 17 . . . ft., Dia in. to . . . ft., Dia in. to . . . ft.

Casing height above land surface 0 . . . in., weight lbs./ft. Wall thickness or gauge No. sch. 40

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)
			9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS: From 17 . . . ft. to 32 . . . ft., From ft. to ft.

From ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 15 . . . ft. to 32 . . . ft., From ft. to ft.

From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 0 ft. to 13 ft., From 13 ft. to 15 ft., From ft. to ft.
What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
13 Insecticide storage
Direction from well? Northeast How many feet? 500

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	Cly, drk brn, ext slty, powdered, dry			
4	9	Snd, v f-med grnd, frly well srted, yell-brn, v slty, damp			
9	12	Snd, v f-med grnd, mod c grns, sl grvl, damp, yell-brn clrd, prly srted			
12	16	Snd, f-c grnd, prly srted, w/ mod grvl, prly srted, yell-brn clrd			
16	20	Snd, a.a. but moist			
20	28	Snd, f-c grnd, mod grvl & rck up to 3/4" in sz, prly srted, yell-brn clrd			
28	32	Snd a.a. but sl grvl & no rck, w/ sl cly yell-brn clrd			
					MW8 - Flushmount

7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-10-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 10-24-94 under the business name of GeoCore Services, Inc. by (signature) Dale Robb