			WATER	WELL RECORD	Form WW	/C-5 P	(SA 82a-					
1 LOCATI		TER WELL:	Fraction			Section !			p Number	Range Nu		
County:	For		SW 1/4	SW 1/4 NW		3	6	T	26 s	I R 2	25 p/w)	
Distance a		from nearest town o				-						
		ortheast of the 1			. Second	Ave						
2 WATE	R WELL OV	vner: Robe	ert Rostetter	•						•		
RR#, St.	Address, Bo	× # : 302	South Second	i St.				Board	of Agriculture,	Division of Water	Resource	
City, State	, ZIP Code	: Dodo	ge City, Kans	sas				Applica	ation Number:			
3 LOCATI	E WELL'S L	OCATION WITH 4 De	DEPTH OF CO	MPLETED WELL		ft.	ELEVAT	ION:				
- AN "X"	IN SECTIO	N BOX:	pth(s) Groundwa	ater Encountered	1 2!	5	ft. 2.		ft,	3		
7	1	I WE	LL'S STATIC V	VATER LEVEL . 3	3.40	ft. below	land surfa	ace measured	d on mo/day/yr			
	1			est data: Well war								
-	NW	NE Est	. Yield	gpm: Weil wai	ter was		ft. aft	er	hours p	umping	apm	
	(i	Bor	re Hole Diamete	or7.5/8in. to	,	2	ft., a	nd	ir	n. to		
¥ W	1			R TO BE USED AS: 5 Public water sup								
7	1	1	1 Domestic	3 Feedlot	6 Oil field	water su	pply 9	Dewatering	12	Other (Specify b	elow)	
-	SW	SE	2 Imigation	4 Industrial	7 Lawn a	nd garder	only (10	Monitoring	well			
	i	Wa	s a chemical/ba	cteriological sample								
1		mit				•		er Well Disinfo	-	No		
5 TYPE C	OF BLANK	CASING USED:		5 Wrought iron	8 Co	ncrete tile	•	CASING	JOINTS: Glue	ed Clampe	ed	
		3 RMP (SR)		Asbestos-Cement	9 Ot	her (spec	ify below))	Weld	ded	. <i>.</i>	
(2)PV		4 ABS		7 Fiberglass			-	, 	Thre	aded X		
		2in.								in. to	ft.	
		and surface										
-	-	R PERFORATION M		, .		PVC			Asbestos-cem			
1 Ste		3 Stainless ste		Fiberglass		RMP (SF	3))		
2 Brass 4 Galvanized steel				6 Concrete tile 9 AE						e used (open hole)		
		RATION OPENINGS		5 Gauzed wrapped			8 Saw cut 11 None (open ho			hole)		
	ontinuous slo	A			wrapped			9 Drilled hol	es	(,	
	uvered shut			7 Torc								
		ED INTERVALS:	From	17 ft. to .		2	.ft From	1	ft.	to		
				ft. to .								
c.	BRAVEL PA			15 ft. to .								
_			From				ft., From				ft.	
6 GROUT	MATERIAL	: 1 Neat ceme	ent (2	Cement grout	(3 B	entonite	4 C	Other				
Grout loter	rvals: Fro	m0ft. t	<u>13</u>	ft., From		ft. to	15	ft., From	1 <i></i>	ft. to		
		ource of possible con				10 Livestock pens 14 Abandoned water well				well		
1 Se	ptic tank	4 Lateral lin	nes				11) Fuel storage 15 Oil well/Gas well					
	wer lines	5 Cess poo		8 Sewage lagoon			12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit				9 Feedyard			13 Insecticide storage					
Direction for	-	South	•				How many feet? 130					
FROM	ТО		ITHOLOGIC LO)G	FROM		_		PLUGGING	INTERVALS		
0	6"	Asphalt										
6"	5.5	Cly, med gry, v	slty, mod-v	sndy, f-v f tr	· med∽							
		c grns										
5.5	12	Snd, v f-med gr	nd, subrnd-s	ubang, well srt	d							
		v slty, damp, l										
12	16	Snd, f-c grnd,		k gry, damp, pr	1y							
		srtd										
16	20	Snd, v f-med ar	and, frly wel	1 srtd, tr of	c							
		grns, lt gry, r										
20	27	Snd, f-c grnd,		ly srtd, yell-								
		brn clrd										
27	32	Snd. f-c grnd, tr of grvl, prly srtd, sub			rndi							
	- VE	subang, sl cly										
		TANAMIA SI SIY		MACT.				MW9 - F	Tushmount			
					١.,							
7 0017	ACTORIC (OR LANDOWNER'S	CERTIFICATION	d: This water well o	vas (1) non	etructed	(2) recon	estructed or /	3) alugaed us	der my jurisdiction	n and was	
		year)										
		year)							, seek of my Ki	.c.mooge and bell	J. Hailbas	
	business na		Services. I		TON CHOCOIG		ipieted of (signatu		20	Roll		
		rpewriter or ball point pen.	•		lease fill in bla				ers. Send too three	copies to Kansas De	partment	