

1 LOCATION OF WATER WELL: COUNTY: FORD		Fraction SE 1/4 SE 1/4 SW 1/4	Section Number 28	Township Number T 26 S	Range Number R 25 E												
Distance and direction from nearest town or city street address of well if located within city? WEST PARK DODGE CITY, KS 67801-																	
2 WATER WELL OWNER: GERMAN, CARL Rt. St. Address, Box #: E.R. 3 -- BOX 49 City, State, ZIP code: WELLINGTON, KS 67152-		Board of Agriculture, Division of Water Resources Application Number:															
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 175 ELEVATION: 0 Depth(s) Groundwater Encountered 1. 0 ft. 2. 0 ft. 3. 0 ft.															
<div style="display: flex; align-items: center;"> <div style="writing-mode: vertical-rl; transform: rotate(180deg); margin-right: 5px;">1 mile</div> <table border="1" style="border-collapse: collapse; text-align: center;"> <tr><td></td><td>NW</td><td>NE</td></tr> <tr><td>W</td><td></td><td></td></tr> <tr><td></td><td>SW</td><td>SE</td></tr> <tr><td></td><td></td><td></td></tr> </table> </div>			NW	NE	W				SW	SE				WELL'S STATIC WATER LEVEL 40 ft. below land surface measured on no/day/yr 11/07/94 Pump test data: Well water was 0 ft. after 0 hours pumping 0 gpm Estimated Yield 60 gpm: Well water was 0 ft. after 0 hours pumping 0 gpm Bore Hole Diameter 9 in. to 175 ft., and in. to 0 ft. WELL WATER TO BE USED AS: DOMESTIC			
			NW	NE													
		W															
			SW	SE													
Was a chemical/bacteriological sample submitted to department? No; If yes, no/day/yr sample was submitted Water well disinfected? Yes																	
5 TYPE OF BLANK CASING USED: PVC CASING JOINTS: GLUED Blank casing diameter 5 in. to 175 ft., Dia in. to 0 ft., Dia in. to 0 ft. Casing height above land surface 12 in., weight 200 lbs/ft. Wall thickness or gauge No. 21 TYPE OF SCREEN OR PERFORATION MATERIAL: PVC SCREEN OR PERFORATION OPENINGS ARE: SAW CUT																	
SCREEN PERFORATED INTERVALS: From 150 ft. to 170 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. GRAVEL PACK INTERVALS: From 24 ft. to 175 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft.																	
6 GROUT MATERIAL BENTONITE Grout intervals: From 4 ft. to 24 ft., From 0 ft. to 0 ft., From 0 ft. to 0 ft. What is the nearest source of possible contamination: SEPTIC TANK Direction from well? SOUTH How many feet? 100																	
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLOGGING INTERVALS												
0	3	TOPSOIL															
3	30	SAND GRAVEL															
30	110	FINE SAND CLAY LAYERS CALACHIE															
110	170	FINE - MED SAND GRAVEL															
170	173	YELLOW CLAY															
173	180	BLUE SHALE															
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed under my jurisdiction and was completed on (no/day/year) 11/15/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 179 This Water Well Record was completed on (no/day/yr) 12/09/94 under the business name of JOE'S WELL SERVICE, INC. by (signature) <i>Justin C. C.</i>																	