

1 LOCATION OF WATER WELL:		Fraction SE ¼ SE ¼ SW ¼		Section Number 26	Township Number T 26 S	Range Number R 25 EW							
County: FORD													
Distance and direction from nearest town or city street address of well if located within city? 710 W. TRAIL ST. DODGE CITY, KANSAS													
2 WATER WELL OWNER: DODGE CITY COOP													
RR#, St. Address, Box # : 710 W. TRAIL ST. DODGE CITY, KS. 67801													
City, State, ZIP Code													
Board of Agriculture, Division of Water Resources Application Number:													
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 35 ft. ELEVATION:											
<div style="text-align: center;">N 1 Mile W E S X</div>		Depth(s) Groundwater Encountered 1. 28 ft. 2. ft. 3. ft.											
		WELL'S STATIC WATER LEVEL 28 ft. below land surface measured on mo/day/yr											
		Pump test data: Well water was ft. after hours pumping gpm											
		Est. Yield gpm: Well water was ft. after hours pumping gpm											
Bore Hole Diameter 7 1/4 in. to 3.5 ft. and in. to ft.		WELL WATER TO BE USED AS:											
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)		5 Public water supply 8 Air conditioning 11 Injection well											
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well		X SPARGE POINT											
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted		Water Well Disinfected? Yes No											
5 TYPE OF BLANK CASING USED:													
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped													
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded													
Blank casing diameter 1 1/4 in. to 33 ft. Dia in. to ft. Dia in. to ft.													
Casing height above land surface 0.3 in. weight sched 40 lbs./ft. Wall thickness or gauge No.													
TYPE OF SCREEN OR PERFORATION MATERIAL:													
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement													
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)													
12 None used (open hole)													
SCREEN OR PERFORATION OPENINGS ARE:													
1 Continuous slot 2 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)													
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes													
7 Torch cut 10 Other (specify)													
SCREEN-PERFORATED INTERVALS: From 35 ft. to 33 ft. From ft. to ft.													
From ft. to ft. From ft. to ft.													
GRAVEL PACK INTERVALS: From 35 ft. to 32 ft. From ft. to ft.													
From ft. to ft. From ft. to ft.													
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other													
Grout Intervals: From 30 ft. to 0.6 ft. From ft. to ft. From ft. to ft.													
What is the nearest source of possible contamination:													
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well													
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well													
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)													
13 Insecticide storage													
Direction from well? NW How many feet? 330													
FROM		TO		LITHOLOGIC LOG			FROM		TO		PLUGGING INTERVALS		
0		0.6		CONCRETE									
0.6		5		TOPSOIL									
5		10		BRN CLAY									
10		15		BRN TAN CLAYEY SAND									
15		20		FINE SAND									
20		25		FINE TO MEDIUM SAND STAINING AT 24									
25		30		MEDIUM SAND SATURATED AT 28									
30		35		MEDIUM TO COARSE SAND									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-8-94 and this record is true to the best of my knowledge and belief. Kansas													
Water Well Contractor's License No. 575 This Water Well Record was completed on (mo/day/yr) 1-3-95													
under the business name of KURTZ ENVIRONMENTAL SERVICE by (signature)													