

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Ford</u> <u>029</u> <u>NE 1/4 SE 1/4 SE 1/4</u>			<u>27</u>	<u>T 26 S</u>	<u>R 25 E</u>
Distance and direction from nearest town or city street address of well if located within city? <u>1520 West Wyath Fair Blvd Dodge City, KS MW # 16</u>					
2 WATER WELL OWNER: <u>FINA OIL &amp; Chemical Co</u>		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #: <u>RD Box 2159</u>		Application Number:			
City, State, ZIP Code: <u>Dallas TX 75221</u>					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>60</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered <u>1</u> <u>40</u> ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>40</u> ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter <u>7 1/4</u> in. to <u>60</u> ft. and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only <input checked="" type="checkbox"/> Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped					
<input checked="" type="checkbox"/> PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded					
7 Fiberglass Threaded					
Blank casing diameter <u>2</u> in. to <u>20</u> ft. Dia in. to ft. Dia in. to ft.					
Casing height above land surface <u>-3</u> in., weight <u>Sch 40</u> lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)					
12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot <input checked="" type="checkbox"/> Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From <u>60</u> ft. to <u>40 20</u> ft. From ft. to ft.					
From ft. to ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>60</u> ft. to <u>18</u> ft. From ft. to ft.					
From ft. to ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From <u>17</u> ft. to <u>0.6</u> ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
13 Insecticide storage <u>Abandoned Fuel Storage</u>					
Direction from well? <u>SW</u> How many feet? <u>59</u>					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	15	Br Plastic Clay			
15	25	Br Sandy Clay			
25	40	Br tan Sandy Clay			
40	60	FINE TO MEDIUM SAND SATURATED AT 40'			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <input checked="" type="checkbox"/> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>1-26-95</u> and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. <u>575</u> This Water Well Record was completed on (mo/day/yr) <u>2-7-95</u>					
under the business name of <u>KVITZ ENVIRONMENTAL SERVICE</u> by (signature) <u>[Signature]</u>					