

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Ford</u> <u>029</u>	<u>NE 1/4 SE 1/4 SE 1/4</u>	<u>27</u>	<u>T 26 S</u>	<u>R 25 E</u>

Distance and direction from nearest town or city street address of well if located within city?

1510 West Wyatt Equip Blvd Dodge City KS MNH # 14

2 WATER WELL OWNER: <u>FINA OIL & CHEMICAL</u>	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: <u>P.O. Box 2159</u>	Application Number:
City, State, ZIP Code: <u>Dallas Tx 75221</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>50</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. <u>40</u> ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>40</u> ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter <u>7 1/4</u> in. to <u>50</u> ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only <u>X</u> Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
<u>X</u> PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter <u>2</u> in. to <u>3.5</u> ft., Dia.			11 Other (specify)
Casing height above land surface <u>3</u> in., weight <u>Sched 40</u> lbs./ft. Wall thickness or gauge No.			12 None used (open hole)
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	<u>X</u> Mill slot	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
SCREEN-PERFORATED INTERVALS:			
From <u>50</u> ft. to <u>35</u> ft.			
GRAVEL PACK INTERVALS:			
From <u>50</u> ft. to <u>32</u> ft.			

6 GROUT MATERIAL:	1 Neat cement	<u>X</u> Cement grout	3 Bentonite	4 Other
Grout Intervals: From <u>31</u> ft. to <u>0.6</u> ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	<u>X</u> Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	
Direction from well? <u>East</u>			How many feet? <u>55</u>	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	6"	Asphalt			
6"	15'	Brs Plastic Clay			
15'	25'	Brs tan Sandy Clay			
25'	40'	Brs TAN FINE Sandy Clay			
40'	50'	FINE TO MEDIUM COARSE SAND			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>X</u> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>1-26-95</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>575</u> This Water Well Record was completed on (mo/day/yr) <u>2-21-95</u> under the business name of <u>KURTZ ENVIRONMENTAL SERVICE</u> by (signature) <u>[Signature]</u>
