

1 LOCATION OF WATER WELL:		Fraction NW 1/4 SE 1/4 NW 1/4		Section Number 17	Township Number T	Range Number S 26 R 26 E/W
Distance and direction from nearest town or city street address of well if located within city?						
3/4 MILE WEST HOWELL HWY 50 NORTH SIDE						
2 WATER WELL OWNER:		PAT MEYERS				
RR#, St. Address, Box #		Cimarron, KS.				
City, State, ZIP Code		Application Number:				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 220 ft. ELEVATION:				
		Depth(s) Groundwater Encountered 1. 89 ft. 2. ft. 3. ft.				
		WELL'S STATIC WATER LEVEL 89 ft. below land surface measured on mo/day/yr 9-30-89				
		Pump test data: Well water was ft. after hours pumping gpm				
		Est. Yield gpm: Well water was ft. after hours pumping gpm				
		Bore Hole Diameter 9 1/8 in. to 230 ft. and in. to ft.				
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well				
		Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)				
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well				
		Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted				
		Water Well Disinfected? Yes No				
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped				
1 Steel 3 RMP (SR)		Welded				
PVC 4 ABS		Threaded				
Blank casing diameter 5 in. to 200 ft. Dia in. to ft. Dia in. to ft.						
Casing height above land surface 20 in. weight 250 lbs./ft. Wall thickness or gauge No.						
TYPE OF SCREEN OR PERFORATION MATERIAL:		PVC 10 Asbestos-cement				
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)						
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:		8 Saw cut 11 None (open hole)				
1 Continuous slot Mill slot 6 Wire wrapped 9 Drilled holes						
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)						
SCREEN-PERFORATED INTERVALS: From 200 ft. to 220 ft. From 160 ft. to ft. From ft. to ft.						
GRAVEL PACK INTERVALS: From 160 ft. to 220 ft. From ft. to ft. From ft. to ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout Bentonite 4 Other						
Grout Intervals: From 4 ft. to 86 ft. From 100 ft. to 260 ft. From ft. to ft.						
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well				
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well						
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)						
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage						
Direction from well? Land undeveloped		How many feet?				
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS						
0 5 TOP SOIL						
5 21 GRAY CLAY						
21 33 BROWN SANDY CLAY						
33 66 FINE TO MED SAND AND GRAVEL						
66 94 BROWN SANDY CLAY						
94 105 FINE TO MED SAND AND GRAVEL						
105 135 BROWN SANDY CLAY						
135 147 FINE SAND						
147 160 BROWN CLAY						
160 220 FINE TO MED SAND AND GRAVEL						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-2-89 and this record is true to the best of my knowledge and belief. Kansas						
Water Well Contractor's License No. 172 This Water Well Record was completed on (mo/day/yr) 9-90						
under the business name of Tanager Drilling by (signature) [Signature]						
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.						