

USE TYPEWRITER OR BALL  
POINT PEN-PRESS FIRMLY,  
PRINT CLEARLY.

WATER WELL RECORD  
KSA 82a-1201-1215

Kansas Department of Health and  
Environment-Division of Environment  
(Water well Contractors)  
Topeka, Kansas 66620

1. Location of well:	County	Fraction	Section number	Township number	Range number
	Ford	NE 1/4 SW 1/4 NE 1/4	19	T 26 S R 26 E/W	
2. Distance and direction from nearest town or city: 7 3/4 Miles E and 1/4 mile S of Cimarron. Street address of well location if in city:			3. Owner of well: Allen Nichols R.R. or street: City, state, zip code: Cimarron, Kansas		
4. Locate with "X" in section below: N 1 Mile W E S 1 Mile		Sketch map: Center of the NE 1/4, Sec. 19, T26S, R26W, Ford Co., Kansas		6. Bore hole dia. 28 in. Completion date 10 May 76 Well depth 179 ft.	
5. Type and color of material		From	To	7. Cable tool Rotary Driven Dug Hollow rod Jetted Bored <input checked="" type="checkbox"/> Reverse rotary	
Top soil		0	2	8. Use: Domestic Public supply Industry <input checked="" type="checkbox"/> Irrigation Air conditioning Stock Lawn Oil field water Other	
Coarse sand medium gravel with boulders		2	25	9. Casing: Material Stl Height: Above or below Threaded Welded <input checked="" type="checkbox"/> Surface 12 in. RMP PVC Weight 37 lbs./ft. Dia. 16 in. to 139 ft. depth Wall Thickness: inches or Dia. in. to ft. depth gage No. 219	
Tan clay		25	62	10. Screen: Manufacturer's name Cook Type WW Dia. 16 in. Slot/gauze 1/8 in Length 40 Set between 139 ft. and 179 ft. ft. and ft. Gravel pack? <input checked="" type="checkbox"/> Size range of material 5.3mm	
Fine sand		62	72	11. Static water level: Not test mo./day/yr. ft. below land surface Date pumped	
Tan clay		72	117	12. Pumping level below land surfaces: ft. after hrs. pumping g.p.m. ft. after hrs. pumping g.p.m. Estimated maximum yield 2000 g.p.m.	
Fine to coarse sand		117	136	13. Water sample submitted: mo./day/yr. Yes <input checked="" type="checkbox"/> No Date	
Sandy tan clay and sand streaks		136	139	14. Well head completion: Pitless adapter <input checked="" type="checkbox"/> Inches above grade	
Coarse sand medium to coarse gravel		139	179	15. Well grouted? Yes With: Neat cement <input checked="" type="checkbox"/> Bentonite Concrete Depth: From 0 ft. to 10 ft.	
Black shale		179	180	16. Nearest source of possible contamination: Unk ft. Direction Type Well disinfected upon completion? <input checked="" type="checkbox"/> Yes No	
BROCK 179				17. Pump: Not installed Manufacturer's name Layne & Bowler Model number 12 KH HP 80 Volts Length of drop pipe 140 ft. capacity 1000 g.p.m. Type: <input checked="" type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other	
(Use a second sheet if needed)				20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Layne-Western Co., Inc. 150 Business name License No. Address Garden City, Kansas Signed Date 24 May 1976 Authorized representative	
18. Elevation:	19. Remarks:				
Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input type="checkbox"/> Upland <input checked="" type="checkbox"/> Valley	2555 179 2376 TOPO				

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5