

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County ROCKY FAIRBANKS FORD NW 1/4 NW 1/4 NE 1/4		19	T 26 S	R 26 E/W

Distance and direction from nearest town or city street address of well if located within city?

1 } MILE WEST OF HOWELL ON RIVER ROAD

2 WATER WELL OWNER:	ROCKY GAIRBANKS	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :		Application Number:
City, State, ZIP Code :	CINARRON, KS.	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 200 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 113 ft. below land surface measured on mo/day/yr 7/90 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 9 7/8 in. to 200 ft. and in. to ft. WELL WATER TO BE USED AS: ☒ Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) ☐ Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No ☒ ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes ☒ No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued ☒ Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
☒ PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 5 in. to 170 ft. Dia			Threaded
Casing height above land surface 20 in. weight 200 lbs./ft. Wall thickness or gauge No.			
TYPE OF SCREEN OR PERFORATION MATERIAL:	☒ PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	☒ Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From ft. to ft.	From ft. to ft.	
GRAVEL PACK INTERVALS:	From ft. to ft.	From ft. to ft.	

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	☒ Bentonite	4 Other
Grout Intervals:	From 4 ft. to 25 ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	☒ Feedyard	12 Fertilizer storage
				13 Insecticide storage
Direction from well?				How many feet? FIELD

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	10	FINE SAND			
10	30	COURSE GRAVEL			
30	69	BROWN SANDY CLAY			
69	80	FILNE TO MED SAND (LOOSE)			
80	152	BROWN SANDY CLAY			
152	198	FINE TO MED SAND MIXCED WITH WHITRE ROCK			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/10/90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 172 This Water Well Record was completed on (mo/day/yr) 7.91 under the business name of JONAGAN DRILLING CO. by (signature) <i>[Signature]</i>
--