W	ATER RR#, S	WELL O	VNER: ress, {	Box # :	CCRG P.O. D	RAWE	R 6090	22075-								ter Resou	ırces
A	/N "X"							TH OF COMPL th(s) Groun						2.	0 ft.	3.	0 ft.
١.	i :		j	i i		i	' WELL'S	S STATIC WA	TER LEVEL estdata:	18 f Well wa	t. below ter was	v land s O	urface m ft. afte	easured r O	on mo/ hours	day/yr 1 pumping	11/ 09/9 2 Ogpm
	} 1	N	# !	-: NE			: : Estima	ated Yield	0 gpm	ı: Well w	ater was	6 0	ft. afte	r 0	hours	pumping	0 gpm
	;		:	1 1		} .! F	 Rore	iole Diamet	er	i	n. to	O ft.	, and	in.	to	0 ft.	
			;	: :		i	!	WATER WAS:					,				,
		S	¥	 -\ SE		- }	!										'
	;			! !		;	Was a	chemical/t	antariala				to donor				
1 2	TYPE OBLANK Casing TYPE OBCREEN	F BLAN casing heigh F SCRE OR PE	K CASII diame t abov EN OR RFORAT	- NG USED: ter e land su PERFORATI	02 PVC 2 rface On Mai	in.	to 20 0 in., L: 03 S 01 C	CASIND CASIND Ft., Dia weight	r sample G JOINTS: in 1 lb	THREADE to s/ft. W	itted) Oft., all thic	Dia ckness (in.	₩ate to (er well 	disinfe	cted? No
1 8 0	TYPE OBLANK Casing TYPE O SCREEN	F BLAN casing heigh F SCRE OR PE	K CASII diame t abov EN OR I RFORAT RATED	NG USED: ter e land su PERFORATI ION OPENI	02 PVC 2 rface ON MAI NGS AF	in. FERIA RE:	to 20 o in., L: 03 S O1 C From From From	CASIN CASIN D ft., Dia weight TAINLESS ST	r sample G JOINTS: 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	THREADE to s/ft. W , From , From , From	itted Oft., all thic	Dia ckness (in. or gauge O ft. O ft. O ft.	Wate	er well) ft. 64	disinfe	cted? No
	TYPE OBLANK Casing TYPE O SCREEN SCREEN GROUT GROUT	F BLAN casing heigh F SCRE OR PE PERFO GRAVEL	K CASII diame t abov EN OR RFORAT PACK 2' AL als:	NG USED: ter e land su PERFORATI ION OPENI INTERVALS INTERVALS 2 CEMENT	O2 PVC 2 rface ON MAI NGS AI :	FERIAL	to 20 o in., i.l.: 03 S o 1 Co	CASIND CASIND Ft., Dia weight TAINLESS STONT. SLOT	r sample G JOINTS: 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	THREADE to s/ft. W , From , From , From , From	oft., of of of of of	Dia ckness (t. to t. to t. to	in. or gauge O ft. O ft. O ft.	Wate to (No15	or well	disinfe	cted? No
	YPE O lank asing YPE O CREEN CREEN ROUT Irout	F BLAN casing heigh F SCRE OR PE PERFO GRAVEL MATERI Intervs the	K CASII diame t abov EN OR RFORAT PACK 2' AL als: neares	NG USED: ter e land su PERFORATI ION OPENI INTERVALS INTERVALS 2 CEMENT	O2 PVC 2 rface ON MAI NGS AI : : GROUT O ft. of po	FERIAL	to 20 o in., i.l.: 03 S o 1 Co	CASIND Ft., Dia weight TAINLESS STONT. SLOT 15 ft. to 0 ft. to 13 ft. to	r sample G JOINTS: 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	THREADE to s/ft. W , From , From , From , From	oft., of of of of of	Dia ckness (t. to t. to t. to	in. or gauge Oft. Oft. Oft.	Wate to (No15) ft.	r many fe	
	YPE O llank casing YPE O CREEN CREEN CREEN	F BLAN casing heigh F SCRE OR PE PERFO GRAVEL MATERI Interv s the ion fr	K CASII diame t abov EN OR RFORAT PACK 2' AL als: neares	NG USED: ter e land su PERFORATI ION OPENI INTERVALS INTERVALS 2 CEMENT From t source	O2 PVC 2 rface ON MAI NGS AI : : GROUT O ft. of po	in. FERIA Service to	to 20 o in., i.l.: 03 S o 1 Co	CASIND ft., Dia weight TAINLESS STONT. SLOT 15 ft. to 0 ft. to 13 ft. to 0 ft. to 14 ft. to 15	r sample G JOINTS: 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	THREADE to s/ft. W t., From t., From t., From t., From	oft., of of of of of	Dia ckness (t. to t. to t. to t. to To A	in. or gauge Oft. Oft. Oft. Oft.	Wate to (No15	ft. How		
7 in in 17	YPE 0 lank asing YPE 0 CREEN CREEN ROUT rout hat i irect	F BLAN casing heigh F SCRE OR PE PERFO GRAVEL MATERI Interv s the ion fr	K CASII diame t abov EN OR RFORAT RATED PACK 22 AL als: neares om wel	NG USED: ter e land su PERFORATI ION OPENI INTERVALS INTERVALS 2 CEMENT From t source	O2 PVC 2 rface ON MAI NGS AI : : GROUT O ft. of po	in. FERIA Service to	to 20 oin., iL: 03 S 01 C From From From From From From From Fro	CASIND ft., Dia weight TAINLESS STONT. SLOT 15 ft. to 0 ft. to 13 ft. to 0 ft. to 14 ft. to 15	r sample G JOINTS: 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	THREADE to s/ft. W t., From t., From t., From t., From	oft., of ft., l	Dia ckness of t. to t. to t. to To 4	in. or gauge Oft. Oft. Oft. Oft. EBACKFI BENTON CAVED	to (No15	or well oft. ft. How	v many fe	
	TYPE OBTAINS TY	F BLAN casing heigh F SCRE OR PE PERFO GRAVEL MATERI Interv s the ion fr	K CASII diame t abov EN OR RFORAT RATED PACK 22 AL als: neares om wel	NG USED: ter e land su PERFORATI ION OPENI INTERVALS INTERVALS 2 CEMENT From t source	O2 PVC 2 rface ON MAI NGS AI : : GROUT O ft. of po	in. FERIA Service to	to 20 oin., iL: 03 S 01 C From From From From From From From Fro	CASIND ft., Dia weight TAINLESS STONT. SLOT 15 ft. to 0 ft. to 13 ft. to 0 ft. to 14 ft. to 15	r sample G JOINTS: 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	THREADE to s/ft. W t., From t., From t., From t., From	oft., of ft., l	Dia ckness of t. to t. to t. to t. to TO	in. or gauge Oft. Oft. Oft. Oft. to BACKFI BENTON CAVED	to (No15	or well oft. ft. How	v many fe	
	TYPE OBLANCE SCREEN GCREEN GROUT Grout What i	F BLAN casing heigh F SCRE OR PE PERFO GRAVEL MATERI Interv s the ion fr	K CASII diame t abov EN OR RFORAT RATED PACK 22 AL als: neares om wel	NG USED: ter e land su PERFORATI ION OPENI INTERVALS INTERVALS 2 CEMENT From t source	O2 PVC 2 rface ON MAI NGS AI : : GROUT O ft. of po	in. FERIA Service to	to 20 oin., iL: 03 S 01 C From From From From From From From Fro	CASIND ft., Dia weight TAINLESS STONT. SLOT 15 ft. to 0 ft. to 13 ft. to 0 ft. to 14 ft. to 15	r sample G JOINTS: 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	THREADE to s/ft. W t., From t., From t., From t., From	oft., of ft., l	Dia ckness of t. to t. t	in. or gauge Oft. Oft. Oft. Oft. EACKFI BENTON CAVED	to (No15	or well oft. ft. How	v many fe	
	YPE O llank casing YPE O CREEN CREEN CREEN	F BLAN casing heigh F SCRE OR PE PERFO GRAVEL MATERI Interv s the ion fr	K CASII diame t abov EN OR RFORAT RATED PACK 22 AL als: neares om wel	NG USED: ter e land su PERFORATI ION OPENI INTERVALS INTERVALS 2 CEMENT From t source	O2 PVC 2 rface ON MAI NGS AI : : GROUT O ft. of po	in. FERIA Service to	to 20 oin., iL: 03 S 01 C From From From From From From From Fro	CASIND ft., Dia weight TAINLESS STONT. SLOT 15 ft. to 0 ft. to 13 ft. to 0 ft. to 14 ft. to 15	r sample G JOINTS: 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	THREADE to s/ft. W t., From t., From t., From t., From	oft., of ft., l	Dia ckness of t. to t. t	in. or gauge Oft. Oft. Oft. Oft. to BACKFI BENTON CAVED	to (No15	or well oft. ft. How	v many fe	