	OWNER: dress, Box # : , ZIP code :			22075-			pard of A		ture, D	MW ivision	•		urces
LOCATE WELL AN "X" IN SI	'S LOCATION WITE	 Н		PTH OF COMPLI pth(s) Ground			ELEVATI	ON: 15	0 ft.	2.	0 ft.	3.	0
1		 	; ; \\ELL ;	'S STATIC WA' Pump to	TER LEVEL estdata: ¥				face me . after			ay/yr umping	11/09/ 0
 	1 1		! Esti	mated Yield	O gpm:	Well wate	er was	0 ft	. after	0 h	ours p	umping	0
i w	-		E   Bore	Hole Diamet	er	in.	to (	ft.,	and	in. t	0	0 ft.	
e i			: WELL	WATER WAS:	10 MONITORI	NG							i
}	S# S	E	}										
Blank casing Casing heig TYPE OF SCR		2 in urface ION MATER	! If y !  n. to O in., NIAL: 03		r sample wa G JOINTS: T in. 1 lbs/	s submit	ted  ft., D		in. t	#ater  o 0	well	disinfe	cted?
TYPE OF BLAI Blank casing Casing heig TYPE OF SCRI SCREEN OR PI	g diameter ht above land s EEN OR PERFORAT ERFORATION OPEN DRATED INTERVAL	2 in urface ION MATER INGS ARE: 	! If y ! o in., RIAL: 03 : 01 From	casing Ca	r sample wa G JOINTS: T in. 1 lbs/	HREADED to O ft. Wall	ft., Di I thickne	ess or	in. t gauge N	#ater  o 0	well	disinfe	cted?
TYPE OF BLAI Blank casing Casing heigi TYPE OF SCRI SCREEN OR PI	g diameter ht above land s EEN OR PERFORAT ERFORATION OPEN DRATED INTERVAL	2 in urface ION MATER INGS ARE:  S:	! If y ! 0 in., RIAL: 03 : 01 From From	es, mo/day/y  CASIN' 15 ft., Dia weight STAINLESS ST CONT. SLOT  10 ft. to 0 ft. to 8 ft. to	r sample wa G JOINTS: T in. 1 lbs/ 15 ft., 0 ft., 15 ft.,	HREADED to O ft. Wall  From From From	ft., Di I thickness Oft.	ess or	in. t gauge N  O ft. O ft.	#ater  o 0	well	disinfe	cted?
TYPE OF BLAI Blank casing Casing heigi TYPE OF SCRI SCREEN OR PI  SCREEN PERFO GRAVEI The ca GROUT MATER GROUT Inter	g diameter ht above land s EEN OR PERFORAT ERFORATION OPEN  DRATED INTERVAL  L PACK INTERVAL	2 in urface 10N MATER INGS ARE: S: S: T GROUT Oft. to	i lf y l l l l l l l l l l l l l l l l l l l	CASIN' 15 ft., Dia weight STAINLESS ST CONT. SLOT  10 ft. to 0 ft. to 8 ft. to 0 ft. to	15 ft., 0 ft., 0 ft. to	HREADED to O ft. Wall  From From From From From O f	ft., Di I thickness Oft.	ia ess or	in. t gauge N O ft. O ft. O ft.	Water 0 0 0 154	ft.	disinfe	cted?
TYPE OF BLAI Blank casing Casing heigi TYPE OF SCRI SCREEN OR PI SCREEN PERFO GRAVE The Ca GROUT MATER GROUT Inter What is the	g diameter ht above land s EEN OR PERFORAT ERFORATION OPEN DRATED INTERVAL L PACK INTERVAL ECING # SCV. IAL 02 CEMEN	2 in urface 10N MATER INGS ARE: S: S: T GROUT 0 ft. to of possi	i lf y l l l l l l l l l l l l l l l l l l l	CASIN' 15 ft., Dia weight STAINLESS ST CONT. SLOT  10 ft. to 0 ft. to 8 ft. to 0 ft. to	15 ft., 0 ft., 0 ft. to	HREADED to O ft. Wall  From From From From From O f	ft., Di I thickness Oft.: Oft.: Oft.:	ia ess or	in. t gauge N O ft. O ft. O ft.	Water 0 0 0 154	ft.	disinfe	
TYPE OF BLAI Blank casing Casing heigi TYPE OF SCRI SCREEN OR PI SCREEN PERFO GRAVE The Ca GROUT MATER GROUT Inter What is the	g diameter ht above land s EEN OR PERFORAT ERFORATION OPEN  DRATED INTERVAL  L PACK INTERVAL	2 in urface ION MATER INGS ARE: S:  T GROUT Oft. to of possi AREA	i lf y l l l l l l l l l l l l l l l l l l l	CASINI 15 ft., Dia weight STAINLESS ST CONT. SLOT  10 ft. to 0 ft. to 8 ft. to 0 ft. to	15 ft., 0 ft., 0 ft. to	From From From From From From From From	ft., Di I thickness O ft. o O ft. o O ft. o Tt., From	TO : 3 : 8 :	in. t gauge N O ft. O ft. O ft. O ft. BACKFIL BENTONI	Water 0 0 0 154 0 ft PLUGGI	ft.  How	many fe	
TYPE OF BLAI Blank casing Casing heigi TYPE OF SCRI SCREEN OR PI SCREEN PERFO GRAVE  The Ca GROUT MATER GROUT Inter What is the Direction f	g diameter ht above land s EEN OR PERFORAT ERFORATION OPEN  DRATED INTERVAL  L PACK INTERVAL  L PACK INTERVAL  L O2 CEMEN vals: From nearest source rom well? LOCAL	2 in urface ION MATER INGS ARE: S:  T GROUT Oft. to of possi AREA	I If y  I to  O in.,  RIAL: 03  From  From  From  From  Strom  From  Fro	CASINI 15 ft., Dia weight STAINLESS ST CONT. SLOT  10 ft. to 0 ft. to 8 ft. to 0 ft. to	15 ft., 0 ft., 0 ft. to	From From From From From From From From	ft., Di I thickner O ft. : O ft. : O ft. : t., From	TO : 3 : 8 :	in. t gauge N O ft. O ft. O ft. O ft. BACKFIL BENTONI	Water 0 0 0 154 0 ft	ft.  How	many fe	
TYPE OF BLAI Blank casing Casing heigi TYPE OF SCRI SCREEN OR PI SCREEN PERFO GRAVE  The Ca GROUT MATER GROUT Inter What is the Direction f	g diameter ht above land s EEN OR PERFORAT ERFORATION OPEN  DRATED INTERVAL  L PACK INTERVAL  L PACK INTERVAL  L O2 CEMEN vals: From nearest source rom well? LOCAL	2 in urface ION MATER INGS ARE: S:  T GROUT Oft. to of possi AREA	I If y  I to  O in.,  RIAL: 03  From  From  From  From  Strom  From  Fro	CASINI 15 ft., Dia weight STAINLESS ST CONT. SLOT  10 ft. to 0 ft. to 8 ft. to 0 ft. to	15 ft., 0 ft., 0 ft. to	From From From From From From From From	ft., Di I thickner O ft. : O ft. : O ft. : t., From	TO : 3 : 8 : 15 :	in. t gauge N O ft. O ft. O ft. O ft. BACKFIL BENTONI	Water 0 0 0 154 0 ft PLUGGI	ft.  How	many fe	
TYPE OF BLAI Blank casing Casing heigi TYPE OF SCRI SCREEN OR PI SCREEN PERFO GRAVE  The Ca GROUT MATER GROUT Inter What is the Direction f	g diameter ht above land s EEN OR PERFORAT ERFORATION OPEN  DRATED INTERVAL  L PACK INTERVAL  L PACK INTERVAL  L O2 CEMEN vals: From nearest source rom well? LOCAL	2 in urface ION MATER INGS ARE: S:  T GROUT Oft. to of possi AREA	I If y  I to  O in.,  RIAL: 03  From  From  From  From  Strom  From  Fro	CASINI 15 ft., Dia weight STAINLESS ST CONT. SLOT  10 ft. to 0 ft. to 8 ft. to 0 ft. to	15 ft., 0 ft., 0 ft. to	From From From From From From From From	ft., Di I thickner O ft. : O ft. : O ft. : t., From	TO   3   8   15   0	in. t gauge N O ft. O ft. O ft. O ft. BACKFIL BENTONI	Water 0 0 0 154 0 ft PLUGGI	ft.  How	many fe	