

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Ford		NW 1/4 NW 1/4 NW 1/4	27	T 26 S	R 26 E <span style="border: 1px solid black; border-radius: 50%; padding: 2px;">W</span>
Distance and direction from nearest town or city street address of well if located within city? Approximately 1 1/4 mile South & 1 mile East of Howell					
2 WATER WELL OWNER:		Biospherics, Incorporated		MW# 5	
RR#, St. Address, Box # :		12051 Indian Creek Court		Board of Agriculture, Division of Water Resources	
City, State, ZIP Code :		Beltsville, Maryland 20705		Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 20 ft. ELEVATION:			
<div style="text-align: center;"> </div>		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 9 ft. below land surface measured on mo/day/yr 7/25/89			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 4 3/4 in. to 2.0 ft. and in. to ft.			
WELL WATER TO BE USED AS:		5 Public water supply    8 Air conditioning    11 Injection well 1 Domestic    3 Feedlot    6 Oil field water supply    9 Dewatering    12 Other (Specify below) 2 Irrigation    4 Industrial    7 Lawn and garden only    10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> X		If yes, mo/day/yr sample was submitted			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel    3 RMP (SR)		6 Asbestos-Cement    9 Other (specify below)    Welded			
2 PVC    4 ABS		7 Fiberglass    Threaded			
Blank casing diameter 2 in. to 2.0 ft. Dia		in. to ft. Dia in. to ft.			
Casing height above land surface 12 in. weight 703 lbs./ft.		Wall thickness or gauge No. 154			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC    10 Asbestos-cement			
1 Steel    3 Stainless steel    5 Fiberglass    8 RMP (SR)    11 Other (specify)		12 None used (open hole)			
2 Brass    4 Galvanized steel    6 Concrete tile    9 ABS					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped    8 Saw cut    11 None (open hole)			
1 Continuous slot    3 Mill slot    6 Wire wrapped    9 Drilled holes					
2 Louvered shutter    4 Key punched    7 Torch cut    10 Other (specify)					
SCREEN-PERFORATED INTERVALS:		From 10 ft. to 20 ft. From ft. to ft.			
GRAVEL PACK INTERVALS:		From 8 ft. to 20 ft. From ft. to ft.			
6 GROUT MATERIAL:		1 Neat cement    2 Cement grout    3 Bentonite    4 Other			
Grout Intervals: From 0 ft. to 8 ft. From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens    14 Abandoned water well			
1 Septic tank    4 Lateral lines    7 Pit privy    11 Fuel storage    15 Oil well/Gas well		12 Fertilizer storage    16 Other (specify below)			
2 Sewer lines    5 Cess pool    8 Sewage lagoon    13 Insecticide storage    None observed		3 Watertight sewer lines    6 Seepage pit    9 Feedyard			
Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top soil.			
2	15	Sand fine to medium.			
15	20	Sand fine to coarse, gravel small to large.			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/25/89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 145 This Water Well Record was completed on (mo/day/yr) 5/23/90 under the business name of Henkle Drilling & Supply Co., Inc. by (signature) Bruce J. Richman					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					