

WATER WELL RECORD		Form WWC-5		KSA 82a-1212	
1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Ford		NW ¼ NW ¼ NW ¼	27	T 26 S	R 26 E
Distance and direction from nearest town or city street address of well if located within city?					
Approximately 1½ mile South & 1 mile East of Howell					
2 WATER WELL OWNER:		Biospherics Incorporated		MW# 2-S	
RR#, St. Address, Box # :		12051 Indian Creek Court		Board of Agriculture, Division of Water Resources	
City, State, ZIP Code :		Beltsville, Maryland 20705		Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 15 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 9 ft. below land surface measured on mo/day/yr 11/16/88			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter . 4 3/4 in. to . 15 ft., and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted			
5 TYPE OF BLANK CASING USED:		Water Well Disinfected? Yes No X			
1 Steel 3 RMP (SR)		Casing Joints: Glued Clamped			
2 PVC 4 ABS		Welded Threaded X			
Blank casing diameter 2 in. to 15 ft., Dia in. to ft.					
Casing height above land surface 12 in., weight 703 lbs./ft. Wall thickness or gauge No. 154					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 10 ft. to 15 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 8 ft. to 15 ft., From ft. to ft.					
FROM		TO		LITHOLOGIC LOG	
0		2		Top soil	
2		15		Fine to coarse sand, small gravel.	
6 GROUT MATERIAL:		2 Cement grout 3 Bentonite 4 Other			
Grout Intervals: From 0 ft. to 8 ft., From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage None observed					
Direction from well?		How many feet?			
FROM		TO		PLUGGING INTERVALS	
0		2			
2		15			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/16/88 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 145 This Water Well Record was completed on (mo/day/yr) 5/23/90 under the business name of Henkle Drilling & Supply Co., Inc. by (signature) Bruce J. Richman					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					