

## CORRECTION(S) TO WATER WELL RECORD (WWC-5)

(to rectify lacking or incorrect information)

County: Ford

Location listed as:

Section-Township-Range: 16-26-26 EFraction (  $\frac{1}{4}$   $\frac{1}{4}$   $\frac{1}{4}$  ): SW SW SE

Location changed to:

16-26-26 WSW SW SE

Other changes: Initial statements: \_\_\_\_\_

Changed to: \_\_\_\_\_

Comments: E changed to Wverification method: County maps, location and address informationinitials: ms date: 3-3-06

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726  
to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
COUNTY: FORD	SW 1/4 SW 1/4 SE 1/4	16	T 26 S	R 26 E

Distance and direction from nearest town or city street address of well if located within city?  
 FROM HOWELL - 1/2 MILES EAST ON HIGHWAY 50

2 WATER WELL OWNER: HOWELL COUNTRY FEEDERS  
 RR#, St. Address, Box #: 10256 W. HIGHWAY 50 Board of Agriculture, Division of Water Resources  
 City, State, ZIP code: DODGE CITY, KS 67801- Application Number: 1

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 185 ELEVATION: 0 Depth(s) Groundwater Encountered 1. 0 ft. 2. 0 ft. 3. 0 ft.
	WELL'S STATIC WATER LEVEL 82 ft. below land surface measured on mo/day/yr 08/11/05 Pump testdata: Well water was 0 ft. after 0 hours pumping 0 gpm Estimated Yield 150 gpm: Well water was 0 ft. after 0 hours pumping 0 gpm Bore Hole Diameter 12 in. to 185 ft., and in. to 0 ft. WELL WATER TO BE USED AS: DOMESTIC Was a chemical/bacteriological sample submitted to department? No; If yes, mo/day/yr sample was submitted Water well disinfected? Yes

5 TYPE OF BLANK CASING USED: PVC CASING JOINTS: GLUED  
 Blank casing diameter 6 in. to 185 ft., Dia in. to 0 ft., Dia in. to 0 ft.  
 Casing height above land surface 12 in., weight 200 lbs/ft. Wall thickness or gauge No. 21  
 TYPE OF SCREEN OR PERFORATION MATERIAL: PVC  
 SCREEN OR PERFORATION OPENINGS ARE: SAW CUT

SCREEN PERFORATED INTERVALS:	From 140 ft. to 180 ft., From 0 ft. to 0 ft.
	From 0 ft. to 0 ft., From 0 ft. to 0 ft.
GRAVEL PACK INTERVALS:	From 26 ft. to 46 ft., From 0 ft. to 0 ft.
	From 56 ft. to 185 ft., From 0 ft. to 0 ft.

6 GROUT MATERIAL BENTONITE  
 Grout intervals: From 5 ft. to 26 ft., From 46 ft. to 56 ft., From 0 ft. to 0 ft.  
 What is the nearest source of possible contamination: NONE  
 Direction from well? How many feet? 0

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	20	01 TOPSOIL 05 CLAY 02 FINE SAND			
20	40	37 FIN-COAR SAN 38 SMAL-MED GRA 05 CLAY			
40	60	05 CLAY 37 FIN-COAR SAN			
60	80	05 CLAY 37 FIN-COAR SAN 14 WHITE CLAY			
80	120	14 WHITE CLAY 32 TAN CLAY			
120	140	14 WHITE CLAY 32 TAN CLAY 10 FINE-MEDSAND			
140	180	37 FIN-COAR SAN 06 SMALL GRAVEL			
180	200	37 FIN-COAR SAN 06 SMALL GRAVEL 07 BLUE SHALE			

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was completed on (mo/day/year) 08/24/05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 179 This Water Well Record was completed on (mo/day/yr) 09/03/05 under the business name of JOB'S WELL SERVICE, INC. by (signature) *Julius Creek*