MW2

WATER WELL RECORD Form WWC-5	Division of Water Resources App. No.
1 LOCATION OF WATER WELL: Fraction	G ( ) Y
County: FOR A NEW	
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here	Global Positioning System (GPS) information:  Latitude: 37, 2739(100) (in decimal degrees)
50' West of 106th Road and 1/8 miles South	Longitude: -/60 . / 6 / 6 / 7. (in decimal degrees)
of Horses hac Road	Elevation: 26 29
	Datum: ☐ WGS 84, ☐ NAD 83, ☐ NAD 27
2 WATER WELL OWNER: USACE RR#, Street Address, Box #: 601 E. 12th Street	Collection Method:  GPS unit (Make/Model:
City, State, ZIP Code : Konsas City, Mo. 64106	☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey
Est. Accuracy:   <3 m,     3-15 m,     >15 m	
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL	195 <sup>-</sup>
SECTION BOX: Depth(s) Groundwater Encountered (1)	
WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr	
Pump test data: Well water was ft. after hours pumping gpm EST. YIELD gpm. Well water was ft. after hours pumping gpm	
w NW NE   EST. YIELD	
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well	
Domestic Feedlot Oil field water supply Dewatering Other (Specify below)	
Irrigation 🔲 Industrial 🔲 Domestic-lawn & garden 👿 Monitoring well	
Was a chemical/bacteriological sample submitted to S If yes, mo/day/yr sample was submitted	
1 mile  Water well disinfected?   Yes   No	
5 TYPE OF CASING USED: Steel PVC Other	
CASING JOINTS: Glued Clamped Welded Threaded	
Casing diameter 4 in to 185 ft., Diameter in to ft., Diameter in to ft.	
Casing height above land surface 30 in., Weight	
TYPE OF SCREEN OR PERFORATION MATERIAL:  ☐ Steel ☐ Stainless Steel ☐ Other (Specify)	
Brass Galvanized Steel None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:	
Continuous slot Mill slot Gauze wrapped Torch cut	☐ Drilled holes ☐ None (open hole)
☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☐ Saw cut SCREEN-PERFORATED INTERVALS: From	ft., From ft. to ft.
GRAVEL PACK INTERVALS: From	ft., From ft. to ft.
GRAVEL PACK INTERVALS: From	P
6 GROUT MATERIAL: Neat cement Cement grout Denton	ft., From ft. to ft.
Grout Intervals: From 180 ft. to 2 ft., From 180 ft. to 183 ft., From ft. to ft.	
What is the nearest source of possible contamination:	
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock p☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage	
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer sto	, , , , ,
Direction from well	from well
FROM TO LITHOLOGIC LOG FROM	TO LITHO. LOG (cont.) or PLUGGING INTERVALS
2 30 brans Clay	
68 80 arm clay	
80 130 arm clan with sand + cravel	
130 145 silty send + grovel	
145 175 I with brown clay with gravel	
175 195 light brum soul some clay layers	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION:, This water	well was X constructed, reconstructed, or plugged
under my jurisdiction and was completed on (mo/day/year)	
Kansas Water Well Contractor's License No This Water Well Record was completed on (mo/day/year)	
under the business name of Boal. Long year. Company.  INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clear	
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.	
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdbeks.gov/waterwell/index.html.	