

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Gray	NE 1/4 SW 1/4 SW 1/4	6	T 26 S	R 27 E

Distance and direction from nearest town or city street address of well if located within city?

From Cimarron, Ks. - 1 mile East on hiway 50 1/2 mile North

2 WATER WELL OWNER: Vic Fisher	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: % Transport Express	Application Number:
City, State, ZIP Code: Wright, Kansas 67882	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL... 238 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL .. 104. ft. below land surface measured on mo/day/yr 6-6-89. Pump test data: Well water was ft. after hours pumping gpm Est. Yield .. 70. gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter .. 10. in. to .. 238. ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No...XX...; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes XX No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued . XX . Clamped .
1 Steel	6 Asbestos-Cement	9 Other (specify below)	Welded .
2 PVC	7 Fiberglass		Threaded .
3 RMP (SR)			
4 ABS			
Blank casing diameter 5. in. to .. 238. ft., Dia. in. to ft., Dia. in. to ft.			
Casing height above land surface 12. in., weight 200. psi. lbs./ft. Wall thickness or gauge No. SDR 21			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	8 RMP (SR)	11 Other (specify)	
2 Brass	9 ABS	12 None used (open hole)	
3 Stainless steel			
4 Galvanized steel			
5 Fiberglass			
6 Concrete tile			
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	
4 Key punched			
SCREEN-PERFORATED INTERVALS: From 194. ft. to 234. ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 40. ft. to 238. ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other hole plug
Grout Intervals: From 5. ft. to 40. ft., From ft. to ft., From ft. to ft.				
What is the nearest source of possible contamination: none new bldg. site	10 Livestock pens	14 Abandoned water well		
1 Septic tank	11 Fuel storage	15 Oil well/Gas well		
2 Sewer lines	12 Fertilizer storage	16 Other (specify below)		
3 Watertight sewer lines	13 Insecticide storage	NA None		
4 Lateral lines				
5 Cess pool				
6 Seepage pit				
7 Pit privy				
8 Sewage lagoon				
9 Feedyard				
Direction from well? NA	How many feet? NA			

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	20	Top soil, cleechie & fine sand			
20	40	Rock layer & fine sand			
40	60	Fine sand			
60	100	Fine sand & some medium sand			
100	120	Fine sand & clay (5 ft.)			
120	140	Clay & fine sand in layers			
140	160	Fine to medium sand			
160	180	Fine sand			
180	200	Fine to medium sand & coarse sand			
200	220	Medium to coarse sand			
220	245	" " "			
245	260	Clay			
260	280	Clay & blue shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-6-89. and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 179. This Water Well Record was completed on (mo/day/yr) 7-17-89
under the business name of Joe's Well Service, Inc. Cimarron, Ks. by (signature) <i>Joe's Well Service</i>