

GRAY

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction NW 1/4 SE 1/4 SE	1/4	Section Number 10	Township Number 27	Range Number R 26 EW
Distance and direction from nearest town or city street address of well if located within city? 4.5 East of Cimarron KS.						
2 WATER WELL OWNER:		WALT Giessel				
RR#, St. Address, Box #:		Rt 2 Dodge City KS 67801				
City, State, ZIP Code		Board of Agriculture, Division of Water Resources Application Number:				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 106 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 40 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 40 ft. below land surface measured on mo/day/yr Pump test data: Well water was NOT PUMPED ft. after hours pumping gpm Est. Yield 50 gpm; Well water was NOT PUMPED ft. after hours pumping gpm Bore Hole Diameter 8 in. to 106 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well LIVESTOCK Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <input checked="" type="checkbox"/> No				
5 TYPE OF BLANK CASING USED:		5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped		
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded		
2 PVC	4 ABS	7 Fiberglass	Threaded		
Blank casing diameter 5 in. to 86 ft., Dia in. to ft., Dia in. to ft.	lbs./ft. Wall thickness or gauge No. SDR 21					
Casing height above land surface 18 in., weight 2.9						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement		
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)		
SCREEN OR PERFORATION OPENINGS ARE:						
1 Continuous slot	Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)		
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	12 None used (open hole)		
SCREEN-PERFORATED INTERVALS: From 86 ft. to 106 ft., From ft. to ft.						
GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft., From ft. to ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other						
Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft., From ft. to ft.						
What is the nearest source of possible contamination: None						
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well		
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well		
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)		
Direction from well?						
FROM	TO	LITHOLOGIC LOG top soil CLAY SAND + GRAVEL CLAY	FROM	TO	PLUGGING INTERVALS	
0	5					
5	35					
35	106					
106						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-23-89 and this record is true to the best of my knowledge and belief. Kansas						
Water Well Contractor's License No. 211 This Water Well Record was completed on (mo/day/yr) 6-15-89 by (signature) John						
under the business name of BRA DRILLING CO.						