


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:	County Gray	Fraction NE $\frac{1}{4}$ SW $\frac{1}{4}$ NE $\frac{1}{4}$	Section number 27	Township number T 26 S	Range number R 27 E/W
2. Distance and direction from nearest town or city: 1 north, $\frac{3}{4}$ NW of Cimarron, Ks.	3 south, 5 east, Street address of well location if in city:	3. Owner of well: Carl Hubble	R.R. or street: Spearville, Ks. 67876		
4. Locate with "X" in section below:	Sketch map: N 		6. Bore hole dia. 26 in. Completion date 4-24-75 Well depth 250 ft.		
			7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input checked="" type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary		
			8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other		
			9. Casing: Material Steel Height: Above ground Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. R.M.P. <input type="checkbox"/> PVC <input type="checkbox"/> Weight 36.07 lbs./ft. Dia. 16 in. to 251 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth Gauge No. <input type="checkbox"/>		
5. Type and color of material	From	To	10. Screen: Manufacturer's name Johnson Division Type Galv. Dia. 16 ¹¹ Slot/gauge Length 20 ¹ Set between 176 ft. and 186 ft. 236 ft. and 246 ft. Gravel pack? <input checked="" type="checkbox"/> Size range of material 1/2" down		
			11. Static water level: 32 ft. below land surface Date 5-28-75		
			12. Pumping level below land surfaces: 60 ft. after 2 hrs. pumping 618 g.p.m. 62 ft. after 4 hrs. pumping 882 g.p.m. Estimated maximum yield 900 g.p.m.		
			13. Water sample submitted: Yes <input checked="" type="checkbox"/> No Date		
			14. Well head completion: Pitless adapter 12 inches above grade		
			15. Well grouted? <input checked="" type="checkbox"/> With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> Concrete Depth From 0 ft. to 10 ft.		
			16. Nearest source of possible contamination: N/A ft. Direction Type Well disinfected upon completion? Yes <input checked="" type="checkbox"/> No		
			17. Pump: Not installed Manufacturer's name Peerless Model number HP Volts Length of drop pipe 170 ft. capacity 800 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other		
(Use a second sheet if needed)			20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Minter-Wilson Drilling Co., 200 Business name <input type="checkbox"/> License No. Address Box 493 Garden City, Ks. Signed <input type="checkbox"/> Date 11-1-1975 Authorized representative <input type="checkbox"/>		
18. Elevation:	19. Remarks: Customer used his own old pump.				
Topography: <input type="checkbox"/> Hill <input checked="" type="checkbox"/> Slope <input type="checkbox"/> Upland <input type="checkbox"/> Valley					

Professionals

MINTER-WILSON DRILLING CO.

INCORPORATED

Water Well Drilling
and Repair Work

Phone 276-8269 • P.O. Box 493 • GARDEN CITY, KANSAS 67846

CARL HUBBELL
Gray County
4-24-75

Location: 600 ft. SW of pivot NE₄ 27-26-27

Test # 2

0	1	Top soil
1	10	Fine sand
10	76	Med. coarse gravel (good loose)
76	95	Brown sandy clay with rock
95	104	Light brown clay
104	110	Fine to med. sand, gravel (loose)
110	121	Brown sandy clay
121	141	Fine to med. sand and gravel (good loose)
141	150	Fine to med. sand and gravel (tight)
150	155	Fine sand
155	170	Fine to med. sand and gravel (little tight)
170	186	Fine to med. sand and gravel (loose)
186	236	Brown sandy clay
236	245	Med. sand, gravel, coarse brown and white rock (tight)
245	250	Brown sandy clay
250	256	Brown, yellow clay
256	258	Blue clay

Static Water Level: 40'

T.D. 250'

20' Screen