


USE TYPEWRITER OR BALL
POINT PEN. PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

| | | | | | | |
|--|--|---|--|--|---------------------------------------|---------------------------|
| County Gray | | Fraction SW 1/4 NE 1/4 SE 1/4 | | Section number 30 | Township number T 26 S R 27 | Range number 27 |
| 2. Distance and direction from nearest town or city: 3 south, 3 east, 1/4 south, 1/4 southeast of Cimarron | | | | 3. Owner of well: Terry Nolan R.R. or street: Cimarron, Ks. 67885 City, state, zip code: | | |
| 4. Locate with "X" in section below: <div style="text-align: center;"></div> | | | | Sketch map: | | |
| 5. Type and color of material | | | | From | To | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| (Use a second sheet if needed) | | | | 6. Bore hole dia. 26 in. Completion date 7-11-76 Well depth 248 ft. | | |
| | | | | 7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary | | |
| | | | | 8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other | | |
| | | | | 9. Casing: Material Steel Height: Above grade 12 in. Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 36.87 lbs./ft. Dia. 16 in. to 249 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. .250 | | |
| | | | | 10. Screen: Manufacturer's name Johnson Type Galv. Dia. 16" Slot 1/8" Length 20 ft. Set between 220 ft. and 240 ft. Perf: 100-220 ft. and 240-248 ft. Gravel pack? yes Size range of material 1/2" down | | |
| | | | | 11. Static water level: 67 ft. below land surface Date 5-20-76 mo./day/yr. | | |
| | | | | 12. Pumping level below land surfaces: 100 ft. after 3 hrs. pumping 750 g.p.m. ft. after <input type="checkbox"/> hrs. pumping <input type="checkbox"/> g.p.m. Estimated maximum yield 750 g.p.m. | | |
| | | | | 13. Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date <input type="checkbox"/> mo./day/yr. | | |
| | | | | 14. Well head completion: <input type="checkbox"/> Pitless adapter 12 inches above grade | | |
| | | | | 15. Well grouted? yes With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft. | | |
| 16. Nearest source of possible contamination: N/A ft. <input type="checkbox"/> Direction <input type="checkbox"/> Type <input type="checkbox"/> Well disinfected upon completion? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No | | | | 17. Pump: <input type="checkbox"/> Not installed Manufacturer's name Goulds - US Pump Model number 12JHC HP 160 Volts <input type="checkbox"/> Length of drop pipe 140 ft. capacity 750 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other | | |
| 18. Elevation: | | 19. Remarks: | | 20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Minter-Wilson Drilling Co. 208 Business name Box A Garden City, Ks. License No. 11-29 <i>[Signature]</i> Authorized representative | | |

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5

MI-1023



MINTER-WILSON DRILLING CO.

INCORPORATED

Irrigation
and Domestic
Water Systems
Complete Installation
and Repairing

Phone 276-8269 • P.O. Box A • GARDEN CITY, KANSAS 67846

TERRY NOLAN

GRAY COUNTY

3/22/77

Location: 30-26-27 $3\frac{1}{2}$ mile south of Cimarron, 2 east, $\frac{1}{2}$ north, $\frac{1}{2}$ west of pivot

Static Water Level- 70'

Test #1

| | | |
|-----|-----|------------------------------|
| 0 | 4 | Top soil |
| 4 | 33 | Brown sandy clay |
| 33 | 153 | Fine to med. sand and gravel |
| 153 | 171 | Brown clay |
| 171 | 248 | Fine to med. sand and gravel |
| 248 | 253 | Brown and yellow clay |
| 253 | 260 | Shale |

T.D. 248

Screen