WATER WELL RECORD		Form W	WC-5	Di	vision of Water	r Resources App. No	),	
1 LOCATION OF WATER WELL:		Fraction		Section	on Number	Township No.		
County: Gray		14 SW14 Sa	1 1/4 SW1/4		<i>⊋</i> 8		R ∠27 □E XW	
Street/Rural Address of		l Positioning	System (GPS) in					
from nearest town or i	owner's address, check		Latitude: (in decimal degrees)					
, and the second se				Longi	Longitude: (in decimal degrees)			
				Eleva	Elevation:			
2 WATER WELL OV	UNED.					I, □ NAD 83, □	NAD 27	
2 WATER WELL OWNER: Terry Nolan RR#, Street Address, Box #: 17908 21 Rd.					Collection Method:  GPS unit (Make/Model:)			
City, State, ZIP Code	7 21 Rd.		☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey					
City, State, Zir Code	70n. Ks. 6835   Est. Accuracy:			5-15 m. $\square > 15$ m				
3 LOCATE WELL						·, · · ·,	<u> </u>	
WITH AN "X" IN		COMPLETED WEL						
SECTION BOX:	Depth(s) Groundwater Encountered (1)							
N	WELL'S STATIC WATER LEVEL/.5.3ft. below land surface measured on mo/day/yr8/3/1.2.							
	Pump test data: Well water was							
W   -NW - NE   EST. YIELD								
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well								
Domestic Feedlot Oil field water supply Dewatering Other (Specify below)								
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well								
S If yes, mo/day/yr sample was submitted								
Water well disinfected? \( \mathbb{X} \) Yes \( \substact \) No								
water went disinfected: 110								
5 TYPE OF CASING USED: Steel PVC Other Other								
CASING JOINTS: Glued Clamped Welded Threaded								
Casing diameter								
Casing height above land surface								
TYPE OF SCREEN OR PERFORATION MATERIAL:  ☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)								
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
☐ Continuous slot 🔀 Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)								
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)								
SCREEN-PERFORATED INTERVALS: From								
From								
GRAVEL PACK INTERVALS: From 34 ft. to 220 ft., From 330 ft. to 510 ft.								
From								
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From ft. to 24 ft., From 12.0 ft. to 330 ft., From ft. to ft.								
	•		<del>حداده</del>	11. 10	. <del></del>	F10III	. 11. 1011.	
What is the nearest source of possible contamination:   Septic tank								
Sewer lines								
Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well								
Direction from well		454		from we	<del>_</del>			
FROM TO	LITHOLOG	IC LOG	FROM	TO	LITHO. LC	OG (cont.) or PLU	GGING INTERVALS	
	Sandy Clay		253	340	Shale 4	Sindstone la	7	
10 30 Tan			340	350	Sands			
		Caliche	350	415	Shak e	+ sandstone	/age CS	
	rse Sand		415	420	Sands	TONC	<u> </u>	
	Sandy clay +		420	440	Shale	<del>-</del> ,		
	Stone & Shal	ح	440	5/0	Sauds	tone		
181 235 Shal								
	stone	1 -			· · · · · · · · · · · · · · · · · · ·			
	e + rock /ec	<del>1755</del>						
250 253 Sandstane								
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was _ constructed, _ reconstructed, or _ plugged under my jurisdiction and was completed on (mo/day/year) 2/1/2. and this record is true to the best of my knowledge and belief.								
under my jurisdiction and was completed on (mo/day/year)								
under the business name of								
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and cleck the powers. Send three copies								
(white, blue, pink) to Kansas I	Department of Health	and Environment, Bureau	of Water, Geol	ogy Sectio	n, 1000 SW Jac	kson St., Sake 420, 1	opeka, Kansas 66612-1367.	
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at								
http://www.kdheks.gov/waterwell/index.html.								
KSA 82a-1212								