WATER WELL RECORD		Form WWC-5		Division of Water Resources App. No.		
	OF WATER WELL:	Fraction		Section Number		Range Number
County: Fo	ord	14 5W 14 SW	/4 NW1/4	9		R 25 DE NW
Street/Rural Ac	idress of Well Location;	f unknown, distance & o	Global Positioning System (GPS) information:			
from nearest town or intersection: If at owner's address, check here			Latitude: (in decimal degrees)			
₹,				Longitude: (in decimal degrees)		
				Blevation:		
2 WATER WE	LL OWNER: /	Smith		Collection Method:	4, [] HVD 62, [J 177327
2 WATER WELL OWNER: Lary Smith RR#, Street Address, Box #: 11344 108 Rd.				GPS unit (Make/Model:)		
City, State, ZIP Code : Dodge city, Ks-67801			Digital Map/Photo, Topographic Map, Land Survey			
(Dodgi	C. 41 10.600		Est. Accuracy:	<3 m, 🔲 3-5 m, 🗀] 5-15 m,
3 LOCATE WELL						
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 65						
SECTION BOX	K: Depth(s) Ground	dwater Encountered (1)	\dots ft. $(2)\dots$,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	(3) II.
WITH AN "X" IN SECTION BOX: N Depth(s) Groundwater Encountered (1)						
Pump test data: Well water wasft. after hours pumping						
EST. YIELDgpm. Well water wasft. afterhours pumpinggpm						
W Bore Hole Diameter The well water supply Geothermal Injection well						
WELL WATER TO BE OBED AS. I I done water supply I documental with						
Oil field water supply Dewatering Other (Specify below) Irrigation Industrial Domestic-lawn & garden Monitoring well						
Was a chemical/bacteriological sample submitted to Department? Yes No						
1						
S If yes, mo/day/yr sample was submitted						
5 TYPE OF CA	SING USED: Stee	PVC DO	ther	raanaan ngamagan gan tis T		
CASING JOINTS: X Glued Clamped Welded Threaded						
Casing diameter fin, Diameter in to ft, Diameter ft, Diam						
Casing hainteed in., Weight in., Weight in., Wall thickness or gauge No. SOR. 21						
TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel PVC Other (Specify)						
Brass Galvanized Steel None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:						
Continuous slot Mill slot						
Louvered shuffer Key nunched Wire wrapped Saw cut Other (specify)						
SCREEN-PERFORATED INTERVALS: From						
From						
GRAVEL PACK INTERVALS: From. 24 ft. to 165 ft., From ft. to						
From ft., to ft., From ft. to						
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other						
Grout Intervals: From						
What is the nearest source of possible contamination: Sentic tank Livestock pens Insecticide storage Other (specify below)						
Sewer lines Cesspool Sewage lagoon Fuel storage Watertight sewer lines Seepage pit Feedyard Fertilizer's				C	gas well	one Observed
Direction from	n well			from well		
FROM TO	LITHOLO	GIC LOG	FROM	TO LITHO.	LOG (cont.) <u>or</u> Pl	LUGGING INTERVAL
0 40	Brown clay					
40 41	Caliche					
41 115	Med-Sand					
115 121	Sandrock					
121 128	Med Sand + be	num clas				
128 163	Course Sand	7				
120 783	Cora Secretaria	the state of the s				
		and the second s				
		A CONTRACTOR OF THE PARTY OF TH				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged						
under my invidiction and was completed on (mo/day/year) and this record is true to the best of my knowledge and belief						
Wansac Water Well Contractor's License No						
under the hydress name of Sant Con Dutter Well by (signature)						
INSTRUCTIONS. He propagates or hall point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three ci						
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1 Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit						
http://www.kdheks.gov/waterwell/index.html.						
KSA 82a-1212						
TENTE OFFICE THEFT						