

County: Gray Fraction: SE SE NW SE Sec. 7 T 26 S R 27 W

CORRECTION(S) TO WATER WELL COMPLETION RECORD (WWC-5) - to rectify lacking or incorrect information

Owner: James Moffitt

If corrected, location was listed as:

Location changed to:

Section-Township-Range: _____

Fraction (1/4 1/4 1/4): _____

Other changes: Initial statements: No "nearest source of possible contamination" given.

Changed to: Abandoned Water Well, North 300 ft.

Comments: _____

Verification method: Correspondence from drilling contractor.

Initials: DRB Date: 10/6/2017

Submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Avenue, Lawrence, KS 66047-3724
 Kansas Dept. of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367

WATER WELL RECORD Form WWC-5

Division of Water Resources App. No.

6574

Well ID

Original Record Correction Change in Well Use

1 LOCATION OF WATER WELL: County: Gray Fraction SE ¼ SE ¼ NW ¼ SE ¼ Section Number 7 Township Number T 26 S Range Number R 27 E W

2 WELL OWNER: Last Name: Moffitt First: James Street or Rural Address where well is located (if unknown, distance and direction from nearest town or intersection): If at owner's address, check here:
 Business: Address: 10566 US Highway 50 1-1/2 miles east of Cimarron on Highway 50/400
 Address: City: Dodge City State: KS ZIP: 67801 south of railroad tracks approximately 1/4 mile.

3 LOCATE WELL WITH "X" IN SECTION BOX:
 N

 W E
 S
 -----1 mile-----

4 DEPTH OF COMPLETED WELL: 190 ft.
 Depth(s) Groundwater Encountered: 1) 82 ft.
 2) ft. 3) ft., or 4) Dry Well
WELL'S STATIC WATER LEVEL: 82 ft.
 below land surface, measured on (mo-day-yr) 03/18/2016
 above land surface, measured on (mo-day-yr)
 Pump test data: Well water was ft.
 after hours pumping gpm
 Well water was ft.
 after hours pumping gpm
 Estimated Yield: 450 gpm
 Bore Hole Diameter: 26 in. to 190 ft. and
 in. to ft.

5 Latitude: 37.799219 (decimal degrees)
Longitude: 100.310979 (decimal degrees)
 Datum: WGS 84 NAD 83 NAD 27
Source for Latitude/Longitude:
 GPS (unit make/model:)
 (WAAS enabled? Yes No)
 Land Survey Topographic Map
 Online Mapper:
6 Elevation: 2598 ft. Ground Level TOC
 Source: Land Survey GPS Topographic Map
 Other KOLAR

7 WELL WATER TO BE USED AS:

1. Domestic: <input type="checkbox"/> Household <input type="checkbox"/> Lawn & Garden <input type="checkbox"/> Livestock	5. <input type="checkbox"/> Public Water Supply: well ID	10. <input type="checkbox"/> Oil Field Water Supply: lease
2. <input checked="" type="checkbox"/> Irrigation	6. <input type="checkbox"/> Dewatering: how many wells?	11. Test Hole: well ID
3. <input type="checkbox"/> Feedlot	7. <input type="checkbox"/> Aquifer Recharge: well ID	<input type="checkbox"/> Cased <input type="checkbox"/> Uncased <input type="checkbox"/> Geotechnical
4. <input type="checkbox"/> Industrial	8. <input type="checkbox"/> Monitoring: well ID	12. Geothermal: how many bores?
	9. Environmental Remediation: well ID	a) Closed Loop <input type="checkbox"/> Horizontal <input type="checkbox"/> Vertical
	<input type="checkbox"/> Air Sparge <input type="checkbox"/> Soil Vapor Extraction	b) Open Loop <input type="checkbox"/> Surface Discharge <input type="checkbox"/> Inj. of Water
	<input type="checkbox"/> Recovery <input type="checkbox"/> Injection	13. <input type="checkbox"/> Other (specify):

Was a chemical/bacteriological sample submitted to KDHE? Yes No If yes, date sample was submitted:
 Water well disinfected? Yes No

8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded
 Casing diameter 16 in. to 190 ft., Diameter in. to ft., Diameter in. to ft.
 Casing height above land surface 18 in. Weight lbs./ft. Wall thickness or gauge No. SCH 40
TYPE OF SCREEN OR PERFORATION MATERIAL:
 Steel Stainless Steel Fiberglass PVC Other (Specify)
 Brass Galvanized Steel Concrete tile None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:
 Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify)
 Louvered Shutter Key Punched Wire Wrapped Saw Cut None (Open Hole)
SCREEN-PERFORATED INTERVALS: From 100 ft. to 190 ft., From ft. to ft., From ft. to ft.
GRAVEL PACK INTERVALS: From 30 ft. to 190 ft., From ft. to ft., From ft. to ft.

9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other
 Grout Intervals: From 0 ft. to 30 ft., From ft. to ft., From ft. to ft.
Nearest source of possible contamination:
 Septic Tank Lateral Lines Pit Privy Livestock Pens Insecticide Storage
 Sewer Lines Cess Pool Sewage Lagoon Fuel Storage Abandoned Water Well
 Watertight Sewer Lines Seepage Pit Feedyard Fertilizer Storage Oil Well/Gas Well
 Other (Specify)
 Direction from well? Distance from well? ft.

10 FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHO. LOG (cont.) or PLUGGING INTERVALS
0	10	Top soil. Brown clay.	135	140	Small medium gravel
10	20	Fine coarse sand. Small medium gravel	140	160	Fine coarse sand. Small medium gravel.
20	40	Fine coarse sand.			Sand, rock, clay layer
40	60	Tan clay. Fine coarse sand.	160	185	Fine sand. Tan clay
60	80	Tan clay. Fine coarse sand w/white caliche	185	200	Blue shale
80	90	Tan clay.			
90	100	Fine coarse sand.	Notes:		
100	125	Fine small grade w/clay streaks.			
125	135	Tan clay. Fine coarse sand streaks.			

11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo-day-year) 03/18/2016 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 846 This Water Well Record was completed on (mo-day-year) 04/12/2016 under the business name of Nash Water Well Service, LLC