	; Section Number ; Township Number ; Range Numbe NE 1/4 ; 04 ; T 26 S ; R 28 W
Distance and direction from nearest town or city st APPROX. 1 3/4 MILES WEST AND 1/2 MILE NORTH OF CIMAN	RRON.
WATER WELL OWNER: SID WARNER RANCH RR#, St. Address, Box # : P.O. BOX 309	Board of Agriculture, Division of Water Resource
	• •
ity, State, ZIP code : CIMARRON, KS 67835-	
OCATE WELL'S LOCATION WITH 4 DEPTH OF CO	OMPLETED WELL 650 ELEVATION: \$2740 P.M.S. roundwater Encountered 1. 203 ft. 2. 0 ft. 3.
; ; ; ; ; WELL'S STATIO	C WATER LEVEL 203 ft. below land surface measured on mo/day/yr 09/2 mp testdata: Well water was 0 ft. after 0 hours pumping
: ! ! ! Estimated Yi	eld 20 gpm: Well water was 0 ft. after 0 hours pumping
# :: E : Bore Hole Di	ameter 17.5 in. to 650 ft., and in. to 0 ft.
	O BE USED AS: 02 IRRIGATION
; SW; SE; ;	
:	al/bacteriological sample submitted to department? No ; ay/yr sample was submitted Water well disinfected
-	dy/y/ Sample was submitted water well distincted
TYPE OF BLANK CASING USED: 02 PVC C Blank casing diameter 8 in. to 650 ft., Casing height above land surface 12 in., we	ASING JOINTS: GLUED Dia in. to Oft., Dia in. to Oft. ight 7 lbs/ft. Wall thickness or gauge No410
TYPE OF BLANK CASING USED: 02 PVC C	ASING JOINTS: GLUED Dia in. to 0 ft., Dia in. to 0 ft. ight 7 lbs/ft. Wall thickness or gauge No410
TYPE OF BLANK CASING USED: 02 PVC C Blank casing diameter 8 in. to 650 ft., Casing height above land surface 12 in., we TYPE OF SCREEN OR PERFORATION MATERIAL: 07 PVC SCREEN OR PERFORATION OPENINGS ARE: 03 MILL SLO	ASING JOINTS: GLUED Dia in. to 0 ft., Dia in. to 0 ft. ight 7 lbs/ft. Wall thickness or gauge No410 T . to 410ft., From 0 ft. to 0 ft.
TYPE OF BLANK CASING USED: 02 PVC Clank casing diameter 8 in. to 650 ft., asing height above land surface 12 in., we type OF SCREEN OR PERFORATION MATERIAL: 07 PVC CREEN OR PERFORATION OPENINGS ARE: 03 MILL SLOCKEEN PERFORATED INTERVALS: From 370ft From 470 ft	ASING JOINTS: GLUED Dia in. to 0 ft., Dia in. to 0 ft. ight 7 lbs/ft. Wall thickness or gauge No410 T . to 410ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft.
TYPE OF BLANK CASING USED: 02 PVC CHIANK casing diameter 8 in. to 650 ft., asing height above land surface 12 in., we type OF SCREEN OR PERFORATION MATERIAL: 07 PVC COREEN OR PERFORATION OPENINGS ARE: 03 MILL SLOCKEEN PERFORATED INTERVALS: From 370ft From 470 ft GRAVEL PACK INTERVALS: From 25 ft	ASING JOINTS: GLUED Dia in. to 0 ft., Dia in. to 0 ft. ight 7 lbs/ft. Wall thickness or gauge No410 T . to 410ft., From 0 ft. to 0 ft.
YPE OF BLANK CASING USED: 02 PVC Clank casing diameter 8 in. to 650 ft., asing height above land surface 12 in., we YPE OF SCREEN OR PERFORATION MATERIAL: 07 PVC CREEN OR PERFORATION OPENINGS ARE: 03 MILL SLOCKEEN PERFORATED INTERVALS: From 370ft From 470 ft GRAVEL PACK INTERVALS: From 25 ft From 320 ft	ASING JOINTS: GLUED Dia in. to 0 ft., Dia in. to 0 ft. ight 7 lbs/ft. Wall thickness or gauge No410 T . to 410ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft to 300 ft., From 0 ft. to 0 ft.
TYPE OF BLANK CASING USED: 02 PVC Clank casing diameter 8 in. to 650 ft., asing height above land surface 12 in., we type OF SCREEN OR PERFORATION MATERIAL: 07 PVC CREEN OR PERFORATION OPENINGS ARE: 03 MILL SLOCKEEN PERFORATED INTERVALS: From 370ft From 470 ft GRAVEL PACK INTERVALS: From 25 ft From 320 ft GROUT MATERIAL 03 BENTONITE GROUT Intervals: From 5 ft. to 25 ft., From 5 ft.	ASING JOINTS: GLUED Dia in. to 0 ft., Dia in. to 0 ft. ight 7 lbs/ft. Wall thickness or gauge No410 T . to 410ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft to 300 ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft.
TYPE OF BLANK CASING USED: 02 PVC Clank casing diameter 8 in. to 650 ft., asing height above land surface 12 in., we type OF SCREEN OR PERFORATION MATERIAL: 07 PVC CREEN OR PERFORATION OPENINGS ARE: 03 MILL SLOCKEEN PERFORATED INTERVALS: From 370ft From 470 ft GRAVEL PACK INTERVALS: From 25 ft From 320 ft From 15 ft. The first four Intervals: From 15 ft. The first full first	ASING JOINTS: GLUED Dia in. to 0 ft., Dia in. to 0 ft. ight 7 lbs/ft. Wall thickness or gauge No410 T . to 410ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft How many feet?
YPE OF BLANK CASING USED: 02 PVC Clank casing diameter 8 in. to 650 ft., asing height above land surface 12 in., we YPE OF SCREEN OR PERFORATION MATERIAL: 07 PVC CREEN OR PERFORATION OPENINGS ARE: 03 MILL SLOCKEEN PERFORATED INTERVALS: From 370ft From 470 ft GRAVEL PACK INTERVALS: From 25 ft From 320 ft From 15 ft. The From 15 ft. T	ASING JOINTS: GLUED Dia in. to 0 ft., Dia in. to 0 ft. ight 7 lbs/ft. Wall thickness or gauge No410 T . to 410ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft.
YPE OF BLANK CASING USED: 02 PVC Clank casing diameter 8 in. to 650 ft., asing height above land surface 12 in., we YPE OF SCREEN OR PERFORATION MATERIAL: 07 PVC CREEN OR PERFORATION OPENINGS ARE: 03 MILL SLOCKEEN PERFORATED INTERVALS: From 370ft From 470 ft GRAVEL PACK INTERVALS: From 25 ft From 320 ft From 320 ft From 320 ft From 5 ft. to 25 ft., From 15 ft. to 25 ft., From 15 ft. The series of possible contamination of the from well? LOCAL AREA	ASING JOINTS: GLUED Dia in. to 0 ft., Dia in. to 0 ft. ight 7 lbs/ft. Wall thickness or gauge No410 T . to 410ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft to 300 ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft. Im 300 ft. to 320 ft., From 0 ft. to 0 ft. How many feet? FROM TO PLUGGING INTERVALS
YPE OF BLANK CASING USED: 02 PVC Clank casing diameter 8 in. to 650 ft., asing height above land surface 12 in., we YPE OF SCREEN OR PERFORATION MATERIAL: 07 PVC CREEN OR PERFORATION OPENINGS ARE: 03 MILL SLO CREEN PERFORATED INTERVALS: From 370ft From 470 ft From 470 ft From 320 ft From 320 ft From 320 ft From 320 ft From 5 ft. to 25 ft., From 320 ft From 5 ft. to 25 ft., From 320 ft SROUT MATERIAL 03 BENTONITE From 5 ft. to 25 ft., From 320 ft SROUT Intervals: From 5 ft. to 25 ft., From 320 ft SROUT Intervals: From 5 ft. to 25 ft., From 320 ft SROUT Intervals: From 5 ft. to 25 ft., From 320 ft SROUT Intervals: From 5 ft. to 25 ft., From 320 ft SROUT Intervals: From 5 ft. to 25 ft., From 320 ft SROUT Intervals: From 5 ft. to 25 ft., From 320 ft SROUT Intervals: From 5 ft. to 25 ft., From 320 ft SROUT Intervals: From 5 ft. to 25 ft., From 320 ft SROUT Intervals: From 5 ft. to 32 ft., From 320 ft SROUT Intervals: From 5 ft. to 32 ft., From 320 ft SROUT Intervals: From 5 ft. to 32 ft., From 320 ft SROUT Intervals: From 5 ft. to 32 ft., From 320 ft SROUT Intervals: From 5 ft. to 32 ft., From 320 ft SROUT Intervals: From 5 ft. to 32 ft., From 320 ft SROUT Intervals: From 5 ft. to 32 ft., From 320 ft SROUT Intervals: From 5 ft. to 32 ft., From 320 ft SROUT Intervals: From 5 ft. to 32 ft., From 320 ft.	ASING JOINTS: GLUED Dia in. to 0 ft., Dia in. to 0 ft. ight 7 lbs/ft. Wall thickness or gauge No410 T . to 410ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft to 500 ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft. Im 300 ft. to 320 ft., From 0 ft. to 0 ft. Im: 09 FEEDYARD How many feet? FROM TO PLUGGING INTERVALS
YPE OF BLANK CASING USED: 02 PVC Clank casing diameter 8 in. to 650 ft., asing height above land surface 12 in., we YPE OF SCREEN OR PERFORATION MATERIAL: 07 PVC CREEN OR PERFORATION OPENINGS ARE: 03 MILL SLOCKEEN PERFORATED INTERVALS: From 370ft From 470 ft From 470 ft From 320 ft From 470 ft From 470 ft From 320 ft From 470 ft From 320 ft From 470 ft From 470 ft From 320 ft From 470 ft From 470 ft From 320 ft From 470 ft From 470 ft From 320 ft	ASING JOINTS: GLUED Dia in. to 0 ft., Dia in. to 0 ft. ight 7 lbs/ft. Wall thickness or gauge No410 T . to 410ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft. Im 300 ft. to 320 ft., From 0 ft. to 0 ft. Im: 09 FEEDYARD FROM TO PLUGGING INTERVALS
TYPE OF BLANK CASING USED: 02 PVC Clank casing diameter 8 in. to 650 ft., asing height above land surface 12 in., we type OF SCREEN OR PERFORATION MATERIAL: 07 PVC CREEN OR PERFORATION OPENINGS ARE: 03 MILL SLOSCREEN PERFORATED INTERVALS: From 370ft From 470 ft GRAVEL PACK INTERVALS: From 25 ft From 320 ft From 320 ft From 5 ft. to 25 ft., From 10 ft From 5 ft. to 25 ft., From 5 ft., F	ASING JOINTS: GLUED Dia in. to 0 ft., Dia in. to 0 ft. ight 7 lbs/ft. Wall thickness or gauge No410 T . to 410ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft To 650 ft., From 0 ft. to 0 ft The same of the same
TYPE OF BLANK CASING USED: 02 PVC Clank casing diameter 8 in. to 650 ft., asing height above land surface 12 in., we type OF SCREEN OR PERFORATION MATERIAL: 07 PVC CREEN OR PERFORATION OPENINGS ARE: 03 MILL SLOW From 370 ft From 470 ft From 470 ft From 320 ft From 5 ft. to 25 ft., From 5 f	ASING JOINTS: GLUED Dia in. to 0 ft., Dia in. to 0 ft. ight 7 lbs/ft. Wall thickness or gauge No410 T . to 410ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft To 650 ft., From 0 ft. to 0 ft The same of the same
TYPE OF BLANK CASING USED: 02 PVC Clank casing diameter 8 in. to 650 ft., casing height above land surface 12 in., we type OF SCREEN OR PERFORATION MATERIAL: 07 PVC CREEN OR PERFORATION OPENINGS ARE: 03 MILL SLO From 370ft From 470 ft From 470 ft From 320 ft From 5 ft. to 25 ft., From 320 ft From 5 ft. to 25 ft., From 320 ft From 5 ft. to 25 ft., From 320 ft From 5 ft. to 25 ft., From 320 ft From 5 ft. to 25 ft., From 320 ft From 5 ft. to 25 ft., From 320 ft From 5 ft. to 25 ft., From 320 ft From 5 ft. to 25 ft., From 320 ft From 5 ft. to 25 ft., From 320 ft From 5 ft. to 25 ft., From 320 ft From 5 ft. to 25 ft., From 320 ft From 5 ft. to 25 ft., From 320 ft From 5 ft. to 25 ft., From 320 ft From 5 ft. to 25 ft., From 320 ft From 5 ft. to 25 ft., From 320 ft From 5 ft. to 25 ft., From 320 ft From 5 ft. to 25 ft., From 320 ft From 5 ft. to 25 ft., From 320 ft From 5 ft. to 25 ft., From 320 ft From 5 ft. to 25 ft., From 320 ft.	ASING JOINTS: GLUED Dia in. to 0 ft., Dia in. to 0 ft. ight 7 lbs/ft. Wall thickness or gauge No410 T . to 410ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft to 300 ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft. where the state of the sta
TYPE OF BLANK CASING USED: 02 PVC Casing height above land surface 12 in., we style of Screen or Perforation Material: 07 PVC Screen or Perforation Openings are: 03 Mill SLO Screen or Perforation Openings are: 03 Mill SLO Screen Perforated Intervals: From 370ft From 470 ft GRAVEL PACK INTERVALS: From 25 ft From 320 ft From 470 ft From 320 f	ASING JOINTS: GLUED Dia in. to 0 ft., Dia in. to 0 ft. ight 7 lbs/ft. Wall thickness or gauge No410 T . to 410ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft to 300 ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft. where the state of the sta
TYPE OF BLANK CASING USED: 02 PVC CBlank casing diameter B in. to 650 ft., Casing height above land surface 12 in., we TYPE OF SCREEN OR PERFORATION MATERIAL: 07 PVC SCREEN OR PERFORATION OPENINGS ARE: 03 MILL SLOW From 470 ft From 470 ft From 320 ft From 5 ft. to 25 ft., From 320 ft From 5 ft. to 25 ft., From 5 ft., Fro	ASING JOINTS: GLUED Dia in. to 0 ft., Dia in. to 0 ft. ight 7 lbs/ft. Wall thickness or gauge No410 T . to 410ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft to 300 ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft to 650 ft., From 0 ft. to 0 ft. where the state of the sta

completed on (mo/day/year) 09/25/91 and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 145
Under the business name of HENKLE DRILLING & SUPPLY
Under the business name of HENKLE DRILLING & SUPPLY
UNDER THE SUPPLY

T

	OF WATER 035 GRAY	WELL:		; Township Number ; T 26 S	; Range Number ; R 28 W
	LL OWNER: Address,	SID WARNER RANCH Box # : P.O. BOX 309	Board of Agriculture, Division of Water Resources		
City, State, IIP code : CIMARRON, KS 67835-			Application Number: 40,238		
FROM ;			i i		
249			. 1		
		: 07 FINE SAND 08 MEDIUM SAND 28 ROCK	i i		
		20 LIMESTONE 19 SHALE] {		
268 ;		: 19 SHALE	i		
304		: 19 SHALE	!		
316		19 SHALE 34 PYRITE	i i		
374		19 SHALE 23 SANDSTONE			
418		19 SHALE			
477		19 SHALE 23 SANDSTONE	i		
514		23 SANDSTONE	i.		
519		19 SHALE 23 SANDSTONE	i		
612 ;		! 19 SHALE 23 SANDSTONE	t I		
648	702	19 SHALE 01 CLAY	•		
1		1	i I		
1		ł i	i I		
i		! !	1		
í		1 1	i i		
1		i i	t i		
;		:	i		
		<u>:</u> !	1		
!		! !	!		
		1	!		
!		: !	!		
		· !	i		
		!	i i		
*		1 1			
1		:	; !		
;		i i	† {		
I I		1 1	! !		
1		1 1	i t		
1		i t	1 4		
į		i t	\$ \$		
í		î Î	; 1		
1		i i	1		
ì		:	1		
i		1	i t		
i		! :	1		
t.		i .	i !		
i			i !		
		t 1	1		

^{;7} CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was ; completed on (mo/day/year) 09/25/91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 145 This Water Well Record was completed on (mo/day/yr) 11/06/91 under the business name of HENKLE DRILLING & SUPPLY