

WATER WELL RECORD Form WWC-5 KSA 82a-1212


1 LOCATION OF WATER WELL:	Fraction NW 1/4 SE 1/4 NE 1/4	Section Number 11	Township Number T 26 S	Range Number R 28 E/W
---------------------------	----------------------------------	----------------------	---------------------------	--------------------------

Distance and direction from nearest town or city street address of well if located within city?

210 East Avenue A, Cimarron, Kansas

2 WATER WELL OWNER:	Grasser Oil Co.	RR#, St. Address, Box #:	210 East Avenue A	Board of Agriculture, Division of Water Resources
City, State, ZIP Code:	Cimarron, KS 67835	Application Number:		

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	N	4 DEPTH OF COMPLETED WELL: 48 ft. ELEVATION: 199.01
	W E	Depth(s) Groundwater Encountered 162.75 ft. 2 ft. 3 ft.
	S	WELL'S STATIC WATER LEVEL 36.26 ft. below land surface measured on mo/day/yr 9/23/92



Pump test data: Well water was ft. after hours pumping gpm			
Est. Yield gpm: Well water was ft. after hours pumping gpm			
Bore Hole Diameter 6 5/8 in. to 49 ft., and in. to ft.			
WELL WATER TO BE USED AS:	5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply	9 Dewatering
2 Irrigation	4 Industrial	7 Lawn and garden only	10 Monitoring well MW#1
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted			
Water Well Disinfected? Yes No X			

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued	Clamped
1 Steel	6 Asbestos-Cement	9 Other (specify below)	Welded	
2 PVC	7 Fiberglass		Threaded	X

Blank casing diameter 2 in. to 28 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface 0.0 in., weight lbs./ft. Wall thickness or gauge No. Sched. 40

TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	8 RMP (SR)	11 Other (specify)
2 Brass	4 Galvanized steel	9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS: From 48' ft. to 28' ft., From ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 48' ft. to 26' ft., From ft. to ft., From ft. to ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals:	From 26 ft. to 24 ft.	From 24 ft. to 0 ft.	From 0 ft. to ft.	From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)

Direction from well?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Clay, Dk. Brn.			
3	8	Clay, Lt. Brn. S1. Silty, Lean			
8	13	Clay, Ms. Brn. Gy. Brn. Silty, Lean			
18	23	Silt, Lt. Brn. Becoming Clay			
23	28	Clay, Md.-Dk. Gray, S1. Sandy, Lean			
28	33	Clay, Md.-Dk. Gray, Very Silty, Lean			
33	38	Clay, Md.-Dk. Gray, Very Mod. Silty			
38	43	Sand, C-M Gr., Dk. Gray			
43	48	Sand, M-C Gr. Gravel, Dk. Gray			
					Flush Mount approved by
					Don Taylor (10-1-92)
					KDHE Code # 01035354

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-8-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 540 This Water Well Record was completed on (mo/day/yr) 11-18-92 under the business name of Prairie Land Environmental Remediation, Inc.

By (signature) *Don Taylor*

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.